



Product Description	Catalog Number
Unassembled Metallic LO-CON™ Fittings Aluminum housing without plates with 3/4" mounting nipple	SC3098
Aluminum housing without plates with 1" mounting nipple	SC3099
Blank stainless steel plate	SS309B
Bushed stainless steel telephone plate 1" I.D. with two 3/8" diameter knockouts for data	SS309T
Single receptacle stainless steel plate 1.390" opening	SS309S
Duplex receptacle stainless steel plate	SS309D
Style Line® or duplex surge receptacle stainless steel plate.	SS309DS

Product Description	Catalog Number
Furniture feed aluminum plate with 1.109" knockout to accept 3/4" liquid-tight or greenfield type connector	SS309SF
Furniture feed aluminum plate, blank <i>Note: When using SS309SF on Hubbell's LO-CON Series Above Floor Fittings, SS309BF must be used on the opposite side.</i>	SS309BF
Assembled Service Fittings IBM-compatible LO-CON fitting. Service Fitting includes the housing with 1" mounting nipple, protector bar, IBM interface plate and stainless steel blank plate.	SC3099C
With telephone bushing and two 3/8" knockouts for data on one side, other side blank.	SC3090
Back-to-back telephone bushings and data openings.	SC3190
One 15-Amp, 125-Volt duplex receptacle, one side blank.	SC3091
Back-to-back 15-Amp, 125-Volt receptacle	SC3092

Note: LO-CON fittings have aluminum housings with stainless steel plates.

Selection Guide

Begin with a Hubbell Plastic Floor Box,
End up with the Precise Service Your Application Requires.
Hubbell Makes it Easy and Complete.

- Step 1**
Order Floor Box
- Step 2**
Order Adapter Ring
(Required for PFB1)
- Step 3**
Select Cover or Above-Floor Service Fitting

