

Straight Blade Devices

INDUSTRIAL



15A, 20A | Traditional Receptacles

Controlled Receptacle Marking

{To comply with 2014 NEC Article 406.3(E)}

To meet the requirements for identifying receptacles that will be automatically de-energized as part of an overall plug load control program, the 2014 National Electrical Code requires all 15A & 20A, 125V receptacles that are automatically controlled to be marked with a specific symbol



Imprinted Receptacles

For new construction and renovation applications, custom imprinting directly on the receptacle is available for our most popular specification grade receptacles. Available in back and side wired and side wired standard, tamper-resistant and Decora® configurations.



5262-1PR



CR015-1PI

Extra Heavy-Duty Spec Grade, Tamper-Resistant, Duplex FED SPEC

Back and Side Wired

| Rating | 15A-125V | 20A-125V | |
|--------------------------------------------------|--------------|----------|----------|
| NEMA | | | |
| | 5-15R | 5-20R | |
| Description | Color | Cat. No. | Cat. No. |
| Hot Terminal Split w/1 Plug Controlled* Markings | White | 5262-1PW | 5362-1PW |
| | Ivory | 5262-1PI | 5362-1PI |
| | Light Almond | 5262-1PT | 5362-1PT |
| | Gray | 5262-1PG | 5362-1PG |
| | Black | 5262-1PE | 5362-1PE |
| | Brown | 5262-1P | 5362-1P |
| | Red | 5262-1PR | 5362-1PR |
| | Blue | 5262-1PB | 5362-1PB |
| 2 Plugs Controlled** Markings | White | 5262-2PW | 5362-2PW |
| | Ivory | 5262-2PI | 5362-2PI |
| | Light Almond | 5262-2PT | 5362-2PT |
| | Gray | 5262-2PG | 5362-2PG |
| | Black | 5262-2PE | 5362-2PE |
| | Brown | 5262-2P | 5362-2P |
| | Red | 5262-2PR | 5362-2PR |
| | Blue | 5262-2PB | 5362-2PB |

Spec Grade, Duplex FED SPEC

Side Wire Only

| Rating | 15A-125V | 20A-125V | |
|-------------------------------------------------|--------------|-----------|-----------|
| NEMA | | | |
| | 5-15R | 5-20R | |
| Description | Color | Cat. No. | Cat. No. |
| Hot Terminal Split, 1 Plug Controlled* Markings | White | CR015-1PW | CR020-1PW |
| | Ivory | CR015-1PI | CR020-1PI |
| | Light Almond | CR015-1PT | CR020-1PT |
| 2 Plugs Controlled** Markings | White | CR015-2PW | CR020-2PW |
| | Ivory | CR015-2PI | CR020-2PI |
| | Light Almond | CR015-2PT | CR020-2PT |

* 1 Controlled = split-circuit - break-off tab removed on 'hot' terminal; control marking on 1 outlet.

** 2 Controlled = no break-off tabs removed; control marking for both outlets

Continued on next page