

RECEPTACLES | Lev-Lok® GFCIs

Lev-Lok® SmartlockPro® GFCI Receptacles

Features and Benefits

- GFCI receptacles have feed-through terminals for downstream protection
- Constructed with impact-resistant PBT cover
- Large triple-wipe, brass “T” line contacts on 20A for superior contact and conductivity
- The SmartlockPro® receptacle automatically tests the GFCI every time the RESET button is pushed. The GFCI will not reset if the GFCI circuit is not functioning properly
- Built-in end-of-life indication. If receptacle can no longer provide GFCI protection, it will not reset and no power will be supplied to the face
- Trip threshold meets or exceeds UL requirements for tripping time
- Right angle wiring module's thin profile makes it easier to place GFCI receptacle in the box
- #12 AWG THHN wire leads, 6" length on MSTWL series wiring modules
- Wiring module locks and latches to the receptacle body providing double the connection security
- Receptacle to be installed only with Leviton MSTWL series wiring modules
- MSTWL wiring module sold separately

SmartlockPro® GFCI Receptacles

2-Pole, 3-Wire Grounding Fed Spec

Rating	15A-125V	20A-125V	
NEMA	5-15R	5-20R	
Description	Color	Cat. No.	Cat. No.
Duplex	White	MN759-HGW	MN789-HGW
	Ivory	MN759-HGI	MN789-HGI
	Light Almond	MN759-HGT	MN789-HGT
	Gray	MN759-HGY	MN789-HGY
	Black	MN759-HGE	MN789-HGE
	Brown	MN759-HG	MN789-HG
	Red	MN759-HGR	MN789-HGR
Duplex, Tamper-Resistant	White	MX759-HGW	MX789-HGW
	Ivory	MX759-HGI	MX789-HGI
	Light Almond	MX759-HGT	MX789-HGT
	Gray	MX759-HGY	MX789-HGY
	Black	MX759-HGE	MX789-HGE
	Brown	MX759-HG	MX789-HG
	Red	MX759-HGR	MX789-HGR



MN759-HGI



MN789-R