

LINEAR FLUORESCENT | Medium, High Output and Slimline

Lampholders

Fluorescent

Medium, High Output and Slimline Linear Fluorescent Lampholders

Features and Benefits

- Silver-plated copper alloy contacts
- Quickwire terminals accept #18 AWG twisted and tinned, solder-dipped or solid leads
- Lampholders are white, starter bases are black

Recessed Double Contact, Pedestal Type Lampholders

For High Output Lamps

| Description | Rating | Cat. No. Plunger | Cat. No. Fixed |
|--|-----------|------------------|----------------|
| Screw Mount, Push-in wiring* | 660W 600V | 13464 | 13465 |
| Same as 13464/13465 except with Internal Shunt Connection for Electronic Ballasts* | 660W 600V | 23464 | 23465 |
| Slide-on, Shallow Base, Quickwire Terminals* | 660W 600V | 13550 | 13551 |
| Slide-on, Shallow Base for Power Groove and Jacketed Lamps, Quickwire Terminals* | 660W 600V | 13556 | 13557 |



13550

For Slimline, Single Pin Lamps

| Description | Rating | Cat. No. Plunger | Cat. No. Fixed |
|--|-------------------------|------------------|----------------|
| Butt-On Surface Mounting, 12" Leads† | 660W 1000V 660W 600V | 452 — | — 453 |
| Pedestal Base, Slide-On | 660W 1000V 660W 600V | 466 — | — 467 |
| Shallow Base, Slide-On or Lock-On Mounting, Quickwire Terminals* | 660W 1000V 660W 600V | 2536 — | — 2537 |



2536

For Medium Bi-Pin Lamps

| Description | Rating | Cat. No. Fixed |
|--|-----------|----------------|
| Thin Body, Quickwire Terminals Accommodate Rapid-Start Circuits | 660W 600V | 431-W |
| Pedestal type, Straight-in Wiring through Wireways or Screw Terminals† | 660W 600V | 390-1W |
| Same as above, with Starter Base† | 660W 600V | 391-1W |



2537

*Suitable for outdoor applications when properly enclosed. NOM Certified except where indicated by †

Starter Bases

For Medium Bi-Pin Lamps

| Description | Rating | Cat. No. |
|---------------------------------------|-----------|----------|
| Starter Base; Screw Terminals, Black† | 660W 250V | 380 |
| Starter Base; with Leads, Black† | 660W 250V | 396 |

NOM Certified except where indicated by †



396

