

Maximum Load for Multi-Gang Applications

Maximum Load			
Cat. No.	Single	2-Gang	3-Gang or more
DSL06	600W Incandescent 300W (2.5A) LED/CFL	500W Incandescent 300W (2.5A) LED/CFL	500W Incandescent 300W (2.5A) LED/CFL
DSM10	1000W Incandescent 1000VA MLV 450W (3.75A) LED/CFL	800W Incandescent 800VA MLV 450W (3.75A) LED/CFL	700W Incandescent 700VA MLV 450W (3.75A) LED/CFL
DSF01	1.5A	1.5A	1.5A
DSE06	480W (4A)	480W (4A)	480W (4A)
DS710 (120V)	960W	960W	960W
DS710 (277V)	1200W	1200W	1200W
DSX10	800W	800W	800W
DSX12	960W	960W	960W
DSH08-1	8A	8A	8A
DSH06-7	6A	6A	6A



DSF01-W

Note: Sharing a neutral wire may cause flickering. Connect all dimmers to the same phase or run a separate neutral to each phase. Consult Leviton Techline if problems persist.

Color Change Kits for Decora® Slide Controls

Color Change Kits			
Description	Cat. No.	Color	
Snap-on frame with slide bar and rocker, locator light in frame	DSKIT-00	W, I, T, G, E, B, R	
Snap-on frame with slide bar and rocker, no locator light	DSKIT-0N	W, I, T, G, E, B, R	

Color

Decora® Slide Controls come packaged with three colors. Products with suffix (-Z) include White, Ivory and Light Almond. Color change kits available in the following colors: Gray (-G), Black (-E), Brown (no suffix) and Red (-R).

SPOTLIGHT

Universal Dimming

Save energy with style by selecting your favorite bulb — incandescent, dimmable LED or dimmable CFL — and take advantage of our suite of online tools to help select the dimmer that's right for you. To access our compatibility charts, online product selector, energy-savings calculator and more, visit www.leviton.com/universal

