


## Connector for Multiple or Overall Shielded Cables Grounded With One Compression



Color-coded marking



Color-coded marking



### Connectors for Shielded Cable

Cat. No.	I.D.	O.D.	Installing Die Cat. No.	Color-Code
<b>Inner Ring</b>				
<b>GSB-430</b>	.430	.500	GS590	Red
<b>GSB-550</b>	.550	.620	GS710	Blue
<b>GSB-670</b>	.670	.750	GS840	Gray
<b>GSB-810</b>	.810	.880	GS1010	Brown
<b>GSB-920</b>	.920	1.000	GS1130	Green
<b>GSB-1040</b>	1.040	1.120	GS1250	Pink
<b>GSB-1122</b>	1.122	1.192	GS1332	Orange
<b>GSB-1224</b>	1.224	1.294	GS1440	Purple
<b>GSB-1353</b>	1.353	1.423	GS1563	Yellow
<b>GSB-1425</b>	1.425	1.545		
<b>Outer Ring</b>				
<b>GSC-590</b>	.590	.670	GS590	Red
<b>GSC-710</b>	.710	.790	GS710	Blue
<b>GSC-840</b>	.840	.920	GS840	Gray
<b>GSC-1010</b>	1.010	1.090	GS1010	Brown
<b>GSC-1130</b>	1.130	1.210	GS1130	Green
<b>GSC-1250</b>	1.250	1.330	GS1250	Pink
<b>GSC-1332</b>	1.332	1.412	GS1332	Orange
<b>GSC-1440</b>	1.440	1.520	GS1440	Purple
<b>GSC-1563</b>	1.563	1.643	GS1563	Yellow
<b>GSC-1670</b>	1.670	1.750		
<b>GSC-1795</b>	1.795	1.875		
<b>GSC-1920</b>	1.920	2.000		

Materials: Inner ring; Copper Alloy ASTM B135, Alloy 2  
Outer ring; Copper ASTM B188

Finish: Electro Tin, MIL-T-10727 A, Type 1. For temp. up to 260°C (500°F), nickel; QQN290.

Note: The inner ring, outer ring and installing die are a matched set.