



E-Z-Ground® Grounding Connectors

Figure 6 Compression Ground Tap Connector





DB
MEETS
IEEE
837 REQUIREMENTS

CAT. NO.	APPLICATION		CABLE TO REBAR APPLICATION		DIMENSIONS (IN.)		DIES FOR TBM 14M, 13100A OR TBM15I
	MAIN	TAP	A GROUND ROD	B CABLE RANGE	T	H	
54855	1/0 Str.-250 kcmil or 1/2"-3/8" Rod	#4 Sol.-#2 Str.	#3 Rebar 3/8" thru 1/2" #4 Rebar	#4 Sol.-#2 Str.	3/4"	1 1/16"	15G86R
54860	1/0 Str.-250 kcmil or 1/2"-5/8" Rod	1/0 Str.-2/0 Str.	#3 Rebar 3/8" thru 1/2" #4 Rebar	1/0 Str.-2/0 Str.	3/4"	2 3/16"	15G86R
54865-CK	1/0 Str.-250 kcmil or 1/2"-5/8" Rod	3/0 Str.-250 kcmil	#3 Rebar 3/8" thru 1/2" #4 Rebar	3/0 Str.-250 kcmil	3/4"	2 3/16"	15G86R
54875	#6 Sol.-#2 Str.	#6 Sol.-#2 Str.	—	—	3/4"	2 3/16"	15501A
54885	250 kcmil-500 kcmil or 5/8"-3/4" Rod	#4 Sol.-#2 Str.	#5 Rebar 5/8" thru 3/4" #6 Rebar	#4 Sol.-#2 Str.	3/4"	1 1/16"	15G126R
54890	250 kcmil-500 kcmil or 5/8"-3/4" Rod	1/0 Str.-2/0 Str.	#5 Rebar 5/8" thru 3/4" #6 Rebar	1/0 Str.-2/0 Str.	3/4"	2 1/8"	15G126R
54895	250 kcmil-500 kcmil or 5/8"-3/4" Rod	3/0 Str.-250 kcmil	#5 Rebar 5/8" thru 3/4" #6 Rebar	3/0 Str.-250 kcmil	3/4"	2 3/16"	15G126R
54900	250 kcmil-500 kcmil or 5/8"-3/4" Rod	350 kcmil-500 kcmil	#5 Rebar 5/8" thru 3/4" #6 Rebar	350 kcmil-500 kcmil	1 3/8"	2 7/16"	15G121R

* Tin-plated version available of galvanized ground rods. Add suffix -TP.

Figure 8 Compression Ground Rod Tap Connector



DB
MEETS
IEEE
837 REQUIREMENTS

CAT. NO.	A GROUND ROD	B CABLE RANGE	DIMENSIONS (IN.)		DIES FOR TBM14M, 13100A OR TBM15I
			T	H	
GR12-202	1/2"	#2 AWG-2/0 AWG	7/8"	1 1/16"	15G121R
GR58-202	5/8"	#2 AWG-2/0 AWG	7/8"	1 3/32"	15G121R
GR34-202	3/4"	#2 AWG-2/0 AWG	7/8"	2 3/16"	15G121R
GR1-202	1"	#2 AWG-2/0 AWG	7/8"	2 3/16"	15G121R
GR12-40250	1/2"	3/0 AWG-250 kcmil	7/8"	1 1/16"	15G121R
GR58-40250	5/8"	3/0 AWG-250 kcmil	7/8"	2 1/8"	15G121R
GR34-40250	3/4"	3/0 AWG-250 kcmil	7/8"	2 3/16"	15G121R
GR1-40250	1"	3/0 AWG-250 kcmil	7/8"	2 3/16"	15G121R
GR58-300500	5/8"	300-500 kcmil	7/8"	2 1/8"	15G121R
GR34-300500	3/4"	300-500 kcmil	7/8"	2 3/16"	15G121R
GR1-300500	1"	300-500 kcmil	7/8"	2 1/16"	15G121R

Tooling: pages F-80-F-100.

Die Selector Chart: pages F-101-F-104.