

## Aluminum Core

### Type ABRH



#### Type ABRH

This non-jacketed flexible aluminum conduit has many universal wiring applications.

#### Construction

Type ABRH is formed from a heavy gauge aluminum strip. Its profile and helical shape allow it to withstand substantial impact and crushing forces.

#### Applications

This conduit is intended as a metal raceway for wires and cable where CSA Certification is required. Suitable for use with connectors intended for FMC (Flexible Metal Conduit).



Conforms to CSA 22.2 No. 56 for use per the Canadian Electrical Code C22.1 Section 12-1300

Trade Size	CSA Metric Desig.	T&B Type	Internal Diameter (in.)		Outer Diameter (in.)		Inside Bend Radius	WT. Lbs. per 100 Ft.	Coil Length Mtr.
			Min.	Max.	Min.	Max.			
3/8	12	ABRH038	0.375	0.393	0.560	0.610	2	7	30, 150, 300
7/16	14	ABRH716	0.437	0.457	-	0.675	2.25	8	30, 150, 300
1/2	16	ABRH050	0.625	0.645	0.860	0.920	3	16	30, 150, 300
3/4	21	ABRH075	0.812	0.835	1.045	1.105	4	18	30, 150, 300
1	27	ABRH100	1.000	1.040	1.300	1.380	5	35	15, 120
1-1/4	35	ABRH125	1.250	1.300	1.550	1.630	6.2	43	15, 120
1-1/2	41	ABRH150	1.500	1.575	1.850	1.950	7.5	55	8, 15, 30
2	53	ABRH200	2.000	2.080	2.350	2.454	10	73	8, 15
2-1/2	63	ABRH250	2.500	2.700	2.860	3.060	12.5	90	8, 15
3	78	ABRH300	3.000	3.200	3.360	3.560	15	107	8, 15
4	103	ABRH400	4.000	-	4.360	4.560	20	142	8, 15