




# Blackburn® mechanical connectors Copper mechanical connectors

Type BTC — copper single-conductor one-hole mount lug with offset tang



Cat. No.	Fig. no.	Conductor range (Cu)		Dimensions (in.)					
		Max.	Min.	L	W	H	F	E	D
BTC1014*	1	#10	#14	1	5/16	43/64	5/64	5/32	3/16
BTC0614	2	#6 Str.	#14	1 3/32	3/8	29/32	5/64	13/64	7/32
BTC0208	2	#2 Str.	#8 Str.	1 15/32	1/2	27/32	3/32	17/64	1/4
BTC1102	2	1/0 Str.	#2 Str.	1 25/32	5/8	1 13/32	1/8	17/64	7/16
BTC3104	2	3/0 Str.	#4 Str.	2 3/64	3/4	1 9/16	1/8	13/32	7/16
BTC4102	2	4/0 Str.	#2 Str.	2 9/16	1	1 61/64	1/8	1 1/32	1/2
BTC3511	2	350	1/0 Str.	3 1/4	1	2 1/2	3/16	13/32	5/8
BTC5011	2	500	1/0 Str.	4 1/4	1 1/2	2 21/32	3/16	13/32	15/16
BTC9960	2	1000	600	4 3/4	2	3 9/16	1/4	17/32	1 1/8

\* Not CSA Certified.