

Applicable cat. no. use for following products	Conductor size AWG or kcmil	Symbol for W	
		Strand./ compr.	Compt./ solid.
Table W10			
35PCJ-1	0.850	1.050	H
35PCJ-2	0.980	1.180	J
	1.090	1.310	K
	1.180	1.465	L
	1.370	1.630	M
	1.515	1.780	N
	1.725	1.935	P
	1.900	2.120	Q

Table W16			
252LR	0.575	0.740	A
252LRJS	0.635	0.905	B
	0.805	1.060	C
	0.890	1.220	D
	1.090	1.310	E

Applicable cat. no. use for following products	Conductor size AWG or kcmil	Symbol for X	
		Strand./ compr.	Compt./ solid.
Table X1			
167/168ELR/DELRL	#2	220	210
273/274ELR/DELRL	#1	230	220
156LR, 161/162LR	#1	230	220
261/262LR, 167LRT	1/0	240	230
167/168RLR, 167DLR	1/0	240	230
273/274RLR, 273DLR	2/0	250	240
00400, 02500	3/0	260	250
02509, 02702	3/0	260	250
02800, K151SP/SR	4/0	270	260
375LR/376LR	4/0	270	260
	250	—	270

Table X2			
375/376LR	1/0	240	230
	2/0	250	240
	3/0	260	250
	4/0	270	260

Table X6			
655/656LRTP	—	#2	210
K655/656LRTP	#2	#1	220
755/756LRTP	#2	#1	220
K656I/Y/H	#1	1/0	230
K655/656LR	1/0	2/0	240
755/756LR	1/0	2/0	240
K655/656SR	2/0	3/0	250
655/656LINK	2/0	3/0	250
K655/656LINK	3/0	4/0	260
755/756LINK	3/0	4/0	260
655/656ETP	4/0	250	270
K655/656ETP	250	300	280
755/756ETP	250	300	280
655/656BI-LINK	300	350	290
K655/656BI-LINK	300	350	290
755BI-LINK	350	400	300
655CK, 755CK	400	450	310
655TCK, 03600	400	450	310
03602, 03700, 03702	450	500/550	320
	500	600	330

Applicable cat. no. use for following products	Conductor size AWG or kcmil	Symbol for X	
		Strand./ compr.	Compt./ solid.
Table X6 continued			
K655/656LRTP	550	650	340
755/756LRTP	600	700	350
K656I/Y/H	600	700	350
K655/656LR	650	750/800	360
755/756LR	650	750/800	360
K655/656SR	700/750	900	380
655/656LINK	700/750	900	380
K655/656LINK	800	—	390
755/756LINK	800	—	390
655/656ETP	900	1000	400
K655/656ETP	1000	—	410
755/756ETP	1000	—	410
655/656BI-LINK	—	1250	420
K655/656BI-LINK	1250	—	440
755BI-LINK	1250	—	440
655CK, 755CK	1250	—	440
655TCK, 03600	1250	—	440
03602, 03700, 03702	1250	—	440

Table X7			
15PCJ1	#2	220	210
25PCJ1	#2	220	210
35PCJ1	#1	230	220
15PCJ2	1/0	240	230
25PCJ2	2/0	250	240
35PCJ2	2/0	250	240
	3/0	260	250
	4/0	270	260
	250	280	270
	350	300	290
	500	330	310
	750	380	360
	1000	410	400
	1250	440	420

Table X9			
PCT1	#2	220	210
PCT2	#2	220	210
01000	#1	230	220
01010	1/0	240	230
	2/0	250	240
	3/0	260	250
	4/0	270	260