

Connectors for Nylon Flexible Conduits

GL Tube Clamps

- Used in general machine and installation applications
- High-grade, specially formulated polyamide
- Self extinguishing
- Free from halogens and cadmium

CAT. NO. BLACK	CAT. NO. GRAY	FITS TO CONDUIT SIZE		DIMENSIONS WIDTH	FIXING SCREW
		NW	METRIC		
BGL-07	SGL-07	07	10	25.0	(1) M4
BGL-10	SGL-10	10	12	27.0	(1) M4
BGL-12	SGL-12	12	16	31.0	(1) M4
BGL-17	SGL-17	17	20	39.5	(1) M5
BGL-23	SGL-23	23	25	49.0	(1) M5
BGL-29	SGL-29	29	32	57.0	(1) M6



Temperature range: -40° C to 105° C

GH Tube Clamps

- Used in general machine and installation applications
- High-grade, specially formulated polyamide
- Self extinguishing
- Free from halogens and cadmium
- Nominal widths: 23–95mm

CAT. NO. BLACK	CAT. NO. GRAY	FITS TO CONDUIT SIZE		DIMENSIONS WIDTH	FIXING SCREW
		NW	METRIC		
BGH-23	SGH-23	23	25	58.0mm	(2) M5
BGH-29	SGH-29	29	32	70.0mm	(2) M6
BGH-36	SGH-36	36	40	80.0mm	(2) M6
BGH-48	SGH-48	48	50	94.0mm	(2) M6



Temperature range: -40° C to 105° C;