


# Galvanized Rigid Conduit (GRC) Couplings & Elbows

## Galvanized Rigid Conduit (GRC) Couplings

Certified to Canadian Standards Association Safety Standard CSA C22.2 No.45.1  
 Manufactured in accordance with ANSI C80.1




Trade Size	Metric Designator	Nominal O.D. (A) <sup>2</sup>		Length (B) <sup>1</sup>		Threads Per Inch <sup>1</sup>	Approximate Weight Per 100 Pieces		Standard Package
		in	mm	in	mm		lb	kg	
1/2	16	1.01	25.7	1 5/8	41.3	14	12	5.4	100
3/4	21	1.25	31.8	1 41/64	41.7	14	18	8.2	50
1	27	1.53	38.7	1 31/32	50.0	11 1/2	30	13.6	25
1 1/4	35	1.87	47.5	2 1/32	51.6	11 1/2	37	16.8	25
1 1/2	41	2.16	54.7	2 1/16	52.4	11 1/2	52	23.6	25
2	53	2.65	67.3	2 1/8	54.0	11 1/2	72	32.7	15
2 1/2	63	3.25	82.6	3 3/16	81.0	8	170	77.1	8
3	78	3.87	98.3	3 5/16	84.1	8	210	95.3	6
3 1/2	91	4.50	114.3	3 13/32	86.5	8	340	154.2	6
4	103	4.88	123.8	3 33/64	89.3	8	300	136.1	5
5	129	6.00	152.4	3 61/64	100.4	8	475	215.5	1
6	155	7.20	182.9	4 1/4	108.0	8	765	347.0	1

<sup>1</sup>Minimum requirement as per CSA Standard

<sup>2</sup>For information only, not a requirement as per CSA Standard

## Galvanized Rigid Conduit (GRC) 90 Degree Elbows

Certified to Canadian Standards Association Safety Standard CSA C22.2 No.45.1  
 Manufactured in accordance with ANSI C80.1



Trade Size	Metric Designator	Radius (A) <sup>1</sup>		Offset (B) <sup>2</sup>		Straight (D) <sup>1</sup>		Approximate Weight Per 100 Pieces		Standard Package
		in	mm	in	mm	in	mm	lb	kg	
1/2	16	4	102	5 7/8	149	1 1/2	38	68	30.8	25
3/4	21	4 1/2	114	7	178	1 1/2	38	109	49.4	40
1	27	5 3/4	146	8 3/4	222	1 7/8	48	201	91.2	25
1 1/4	35	7 1/4	184	10 3/4	273	2	51	336	152.4	10
1 1/2	41	8 1/4	210	12 1/4	311	2	51	460	208.7	10
2	53	9 1/2	241	14 1/2	368	2	51	729	330.7	5
2 1/2	63	10 1/2	267	17	432	3	76	1374	623.2	80
3	78	13	330	19 5/8	498	3 1/8	79	2045	927.6	50
3 1/2	91	15	381	22 3/4	578	3 1/4	83	2860	1297.3	50
4	103	16	406	23 7/8	606	3 3/8	86	3519	1596.2	36
5	129	24	610	34 7/8	886	3 5/8	92	6942	3148.9	1
6	155	30	762	45 1/2	1156	3 3/4	95	11960	5425.1	1

<sup>1</sup>Minimum requirement as per CSA Standard

<sup>2</sup>For information only, not a requirement as per CSA Standard

Sizes 2 1/2 (63) and larger shipped in palletized cartons or bulk.

Also available in the following Degrees (60°, 45°, 30°, 22-1/2°, 15° & 11-1/4°)

NOTE: Special orders are non-cancelable, non-returnable and non-refundable.