


Galvanized Rigid Conduit (GRC) Nipples

Galvanized Rigid Conduit (GRC) Nipples (continued)

Certified to Canadian Standards Association Safety Standard CSA C22.2 No.45.1
Manufactured in accordance with ANSI C80.1



Trade Size	Metric Designator	Length (A)		Total Thread Length (B) ¹		Threads Per Inch ¹	Approximate Weight Per 100 Pieces		Standard Package
		in	mm	in	mm		lb	kg	
1	27	(Close) 1 1/2	38	0.98	24.9	11 1/2	16	7.3	25
1	27	2	51	0.98	24.9	11 1/2	22	10.0	25
1	27	2 1/2	64	0.98	24.9	11 1/2	28	12.7	25
1	27	3	76	0.98	24.9	11 1/2	36	16.3	25
1	27	3 1/2	89	0.98	24.9	11 1/2	43	19.5	25
1	27	4	102	0.98	24.9	11 1/2	49	22.2	25
1	27	5	127	0.98	24.9	11 1/2	64	29.0	25
1	27	6	152	0.98	24.9	11 1/2	78	35.4	25
1	27	8	203	0.98	24.9	11 1/2	109	49.4	25
1	27	10	254	0.98	24.9	11 1/2	138	62.6	25
1	27	12	305	0.98	24.9	11 1/2	166	75.3	25
1 1/4	35	(Close) 1 5/8	41	1.01	25.7	11 1/2	22	10.0	25
1 1/4	35	2	51	1.01	25.7	11 1/2	28	12.7	25
1 1/4	35	2 1/2	64	1.01	25.7	11 1/2	37	16.8	25
1 1/4	35	3	76	1.01	25.7	11 1/2	47	21.3	25
1 1/4	35	3 1/2	89	1.01	25.7	11 1/2	55	24.9	25
1 1/4	35	4	102	1.01	25.7	11 1/2	66	29.9	25
1 1/4	35	5	127	1.01	25.7	11 1/2	84	38.1	25
1 1/4	35	6	152	1.01	25.7	11 1/2	100	45.4	25
1 1/4	35	8	203	1.01	25.7	11 1/2	136	61.7	25
1 1/4	35	10	254	1.01	25.7	11 1/2	176	79.8	10
1 1/4	35	12	305	1.01	25.7	11 1/2	216	98.0	10
1 1/2	41	(Close) 1 3/4	44	1.03	26.2	11 1/2	28	12.7	25
1 1/2	41	2	51	1.03	26.2	11 1/2	34	15.4	25
1 1/2	41	2 1/2	64	1.03	26.2	11 1/2	44	20.0	25
1 1/2	41	3	76	1.03	26.2	11 1/2	56	25.4	25
1 1/2	41	3 1/2	89	1.03	26.2	11 1/2	68	30.8	25
1 1/2	41	4	102	1.03	26.2	11 1/2	80	36.3	25
1 1/2	41	5	127	1.03	26.2	11 1/2	103	46.7	25
1 1/2	41	6	152	1.03	26.2	11 1/2	122	55.3	25
1 1/2	41	8	203	1.03	26.2	11 1/2	170	77.1	10
1 1/2	41	10	254	1.03	26.2	11 1/2	216	98.0	10
1 1/2	41	12	305	1.03	26.2	11 1/2	260	117.9	10
2	53	(Close) 2	51	1.06	26.9	11 1/2	44	20.0	25
2	53	2 1/2	64	1.06	26.9	11 1/2	59	26.8	25
2	53	3	76	1.06	26.9	11 1/2	72	32.7	25
2	53	3 1/2	89	1.06	26.9	11 1/2	88	39.9	25
2	53	4	102	1.06	26.9	11 1/2	103	46.7	25
2	53	5	127	1.06	26.9	11 1/2	132	59.9	20
2	53	6	152	1.06	26.9	11 1/2	160	72.6	20
2	53	8	203	1.06	26.9	11 1/2	220	99.8	10
2	53	10	254	1.06	26.9	11 1/2	285	129.3	10
2	53	12	305	1.06	26.9	11 1/2	335	152.0	10



¹Minimum requirement as per CSA Standard

A tolerance of minus one thread applies to Total length of Thread

Chart continued on the next page

NOTE: Special orders are non-cancelable, non-returnable and non-refundable.