

## 555® CX/DX Series Electric Benders

**NEW PRODUCT**



- The 555® Series, commonly referred to as the "triple-nickel", has been completely re-engineered with a rugged exterior for the most demanding environments.

**SIMPLE. 2 SHOES CAN HANDLE 6 SIZES (1/2"-2") RIGID, EMT & IMC**

**ACCURATE. ABSOLUTE-ENCODER BASED CONTROL ON 555DX REDUCES SCRAP & REWORK**

**RELIABLE. MORE UPTIME TO BEND<sup>1</sup>**

<sup>1</sup> Solid-state electronics system rated for 1,000,000+ bends.



**A PRODUCT VIDEO IS AVAILABLE, SCAN THIS QR CODE OR VISIT:**  
[www.youtube.com/GreenleeDEMO](http://www.youtube.com/GreenleeDEMO)



### SPECIFICATIONS

**Capacity** 1/2" - 2" Rigid / EMT / IMC / PVC Coated  
**Power Source** 120 VAC, 20 amp GFCI  
**Weight** 300 lbs.

CAT NO.	UPC NO.	DESCRIPTION
555CX	12425	Bender, Electric Conduit with Standard Pendant (120 VAC, 20A)
555CXE	13972	Electric Bender, with 13930 1/2" - 2" EMT Shoe Group (120 VAC, 20A)
555CXR	12426	Electric Bender, with 28007 1/2" - 2" Rigid Shoe Group (120 VAC, 20A)
555CXRE	12427	Electric Bender, with 12580 1/2" - 2" Rigid, EMT Group (120 VAC, 20A)
555DX	12428	Bender, Electric Conduit with Digital Angle Pendant (120 VAC, 20A)
555DXE	13973	Electric Bender, with 13930 1/2" - 2" EMT Shoe Group (120 VAC, 20A)
555DXR	12429	Electric Bender, with 28007 1/2" - 2" Rigid Shoe Group (120 VAC, 20A)
555DXRE	12430	Electric Bender, with 12580 1/2" - 2" Rigid, EMT Group (120 VAC, 20A)
555DX-22	49840	Electric Bender, with Digital Angle Pendant (220 VAC, 20A)
555DXR-22	49842	Electric Bender, with 28007 1/2" - 2" Rigid Shoe Group (220 VAC, 20A)
A 28007	28007	Shoe Group, 1/2" - 2" Rigid (555 Series)
A 13930	13930	Shoe Group, 1/2" - 2" EMT (555 Series)
A 12580	12580	Shoe Group, 1/2" - 2" Rigid/EMT Combination (555 Series)
A 12581	12581	Shoe Group, 1/2" - 2" PVC Coated Rigid (555 Series)
A 13856	13856	Roller Unit, 1-1/2" - 2" IMC (555 Series) Combination Shoe (use with 12580 shoe group)
A 12583	12583	Roller Unit, 1-1/2" - 2" EMT (555 Series) Single Groove Shoes (use with 23802 and 23816 shoe groups)
A 12584	12584	Roller Unit, 1-1/2" - 2" IMC (555 Series) Single Groove Shoes (use with 26330 shoe group)

CAT NO.	SHOE GROUP	555DX	555CX	555 CLASSIC
12580	Combination 1/2"- 2" EMT/Rigid <sup>1</sup>	✓	✓	
28007	1/2"- 2" Rigid	✓	✓	✓
13930	1/2"- 2" EMT	✓	✓	
23802	1/2"- 2" EMT	✓ <sup>2</sup>	✓ <sup>2</sup>	✓
26330	1-1/2"- 2" IMC	✓ <sup>3</sup>	✓ <sup>3</sup>	✓
12581	1/2"- 2" PVC Coated	✓	✓	
37279	1/2"- 2" PVC Coated	✓	✓	✓
12582	1/2"- 2" PVC Coated	✓ <sup>4</sup>	✓ <sup>4</sup>	
01700	1/2"- 2" PVC Coated	✓ <sup>4</sup>	✓ <sup>4</sup>	

### BENDING RADII COMBO SHOE GROUP

SHOE SIZE	INCHES	mm
1/2" EMT	4-5/16"	109.5
1/2" IMC/Rigid	4-1/4"	108.0
3/4" EMT	5-1/2"	139.7
3/4" IMC/Rigid	5-7/16"	138.1
1" EMT	7"	177.8
1" IMC/Rigid	6-15/16"	176.2
1-1/4" EMT	8-13/16"	223.8
1-1/4" IMC/Rigid	8-3/4"	222.3
1-1/2" EMT	8-3/8"	212.7
2" EMT	9-1/4"	235.0
2" IMC/Rigid	9"	228.6

<sup>1</sup> Can also bend 1/2" - 1-1/4" IMC, need optional 13856 squeeze roller assembly for 1-1/2" & 2" IMC bending.

<sup>2</sup> Need optional 12583 roller unit for 1-1/2" & 2" EMT bending on 555CX & 555DX models.

<sup>3</sup> Need optional 12584 roller unit for 1-1/2" & 2" IMC bending on 555CX & 555DX models.

<sup>4</sup> Need 00946 and 13861 support roller assemblies to bend 1/2" - 2" PVC coated rigid on 555CX & 555DX.