

## Copper Lugs

### Copper Tin-Plated One-Hole Lugs

Tin-plated lugs resist corrosion

- Provides high-conductivity
- Minimizes voltage drop
- Easy identification
- UL Listed and CSA Certified



L 750-48



Cat. No.	Wire Size	Bolt Size	Installing Dies
L 8-10	#8	10	TC, 21, 171, 236
L 8-14		1/4	
L 8-38		3/8	
L 8-48		1/2	
L 6-10	#6	10	7, TE, 24
L 6-14		1/4	
L 6-516		5/16	
L 6-38		3/8	
L 4-10	#4	10	5/16, 8, TP, 29, 161
L 4-14		1/4	
L 4-516		5/16	
L 4-38		3/8	
L 2-14	#2	1/4	3/8, 10, TL-TN, 33, 162
L 2-516		5/16	
L 2-38		3/8	
L 2-48		1/2	
L 1-14	#1	1/4	11, TB, 37
L 1-516		5/16	
L 1-38		3/8	
L 1-48		1/2	
L 1/0-516	1/0	5/16	1/2, 12, TQ, 42, 163
L 1/0-38		3/8	
L 1/0-48		1/2	
L 2/0-516	2/0	5/16	13, TS, 45, 164, 241
L 2/0-38		3/8	
L 2/0-48		1/2	

Cat. No.	Wire Size	Bolt Size	Installing Dies
L 3/0-516	3/0	5-16	5/8, 14, TU, 50, 243, BG
L 3/0-38		3/8	
L 3/0-48		1/2	
L 4/0-516	4/0	5/16	15, TW-TY, 54, 243
L 4/0-38		3/8	
L 4/0-48		1/2	
L 250-38	250	3/8	11/16, 16, TR, 60, 166
L 250-48		1/2	
L 300-38	300	3/8	781, 17, TV, 66
L 300-48		1/2	
L 300-58		5/8	
L 350-38	350	3/8	840, 18, TX, 71
L 350-48		1/2	
L 350-58		5/8	
L 400-48	400	1/2	840, 19, TX, 76
L 400-58		5/8	
L 500-48	500	1/2	20, TH, 87, 281
L 500-58		5/8	
L 600-48	600	1/2	1 (1/8)-1, 96
L 600-58		5/8	
L 750-48	750	1/2	1 (1/8)-2, 106
L 750-58		5/8	
L 750-68		3/4	
L 1000-48	1000	1/2	642, 125
L 1000-58		5/8	
L 1000-68		3/4	