

URD Multi-Port Bus Connectors and Covers



Aluminum Flood-Seal™ 125 Series

Service Entrance Connectors — One- and Two-Hole Types

One-way connectors with rubber insulation or two-way connectors with PVC insulation for #8 to 500 kcmil cable

- Ensures cooler operation and more reliable joints
- Accept standard one- or two-hole NEMA aluminum or copper lugs
- Safe and reliable
- Ensures that connectors are 100% watertight and molded correctly
- All Flood-Seal™ connectors meet or exceed ANSI C119.4
- Approved by the Federal government for utility use

EPDM-Insulated, One-Way Configuration

| Cat. No. | Outlets | L |
|------------|---------|--------|
| FS 21-125 | 3 | 5-3/8 |
| FS 111-125 | 3 | 5-3/8 |
| FS 414-125 | 9 | 16-5/8 |
| FS 31-125 | 4 | 7-1/4 |
| FS 212-125 | 5 | 9-1/8 |
| FS 222-125 | 6 | 11 |
| FS 41-125 | 5 | 9-1/8 |
| FS 313-125 | 7 | 12-7/8 |
| FS 323-125 | 8 | 14-3/4 |

To order insulating sleeves for EPDM One-Way Connectors, see page C29.

PVC-Insulated, Two-Way Configuration

| Cat. No. | Outlets |
|------------|---------|
| FST 125 | 3 |
| FSTT 125 | 5 |
| FSX 125 | 4 |
| FSXX 125 | 6 |
| FSY 125-21 | 3 |
| FSY 125-42 | 6 |
| FSY 125-64 | 10 |

