

## Heavy Duty Panel Mount

### 10A 250V AC 20A 125V AC Horsepower Rated 1½ HP, 125-250V AC

Description	Terminal	Catalog Number
Double pole/ single throw.	Screw Spade	<b>HBL21</b> <b>HBL21SP</b>
Double pole/ single throw.	Screw Spade	<b>HBL22</b> <b>HBL22SP</b>
Double pole/ double throw 3-position center OFF.	Screw Spade	<b>HBL223</b> <b>HBL223SP</b>
Double pole/ double throw 3-position center OFF momentary.	Screw Spade	<b>HBL223MM</b> <b>HBL223SPMM</b>
Silicone rubber boot.	Screw Spade	<b>SSB1</b>



HBL21



HBL223



SSB1

Note: All threaded stems 1/32 in.-32 thread.  
See AA-33 for additional information on 12V DC tapered handle switches.

### 4A 250V 8A 125V 10A 120V AC 1/3 HP 120V AC

Description	Terminal	Catalog Number
Single pole/ single throw.	#18 Std. AWG Copper Wire Leads 105° C Black.	<b>HBL11PBWL</b>



HBL11PBWL

Note: 1/32 in.-32 thread, keyway .080 x .035.

Dimensions in Inches (mm)