

## Surge Protection Devices



15A 125V  
NEMA 5-15R  
UL CSA  
0.5 HP




20A 125V  
NEMA 5-20R  
UL CSA  
1 HP


### Hospital Grade • Circuit Guard® Receptacles

Description	Color	Catalog Number	
SNAPConnect® Tamper-Resistant, surge suppression duplex receptacle, smooth face, 240 joules, 15000A peak current. Requires Snap connector on page M-14, sold separately.	Blue	<b>SNAP8262S</b>	<b>SNAP8362S</b>
	Gray	<b>SNAP8262GYS</b>	<b>SNAP8362GYS</b>
	Ivory	<b>SNAP8262IS</b>	<b>SNAP8362IS</b>
	Light Almond	<b>SNAP8262LAS</b>	<b>SNAP8362LAS</b>
	Red	<b>SNAP8262RS</b>	<b>SNAP8362RS</b>
White	<b>SNAP8262WS</b>	<b>SNAP8362WS</b>	
Surge suppression receptacles with light and alarm, 240 joules, 15000A peak current.	Almond	<b>HBL8262ALSA</b>	<b>HBL8362ALSA</b>
	Blue	<b>HBL8262SA</b>	<b>HBL8362SA</b>
	Gray	<b>HBL8262GYSA</b>	<b>HBL8362GYSA</b>
	Ivory	<b>HBL8262ISA</b>	<b>HBL8362ISA</b>
	Red	<b>HBL8262RSA</b>	<b>HBL8362RSA</b>
White	<b>HBL8262WSA</b>	<b>HBL8362WSA</b>	
Isolated ground, surge suppression receptacles with light and alarm, 240 joules, 15000A peak current.	Blue	<b>IG8262SA</b>	<b>IG8362SA</b>
	Gray	<b>IG8262GYSA</b>	<b>IG8362GYSA</b>
	Ivory	<b>IG8262ISA</b>	<b>IG8362ISA</b>
	Orange	<b>IG8262OSA</b>	<b>IG8362OSA</b>
	Red	<b>IG8262RSA</b>	<b>IG8362RSA</b>
White	<b>IG8262WSA</b>	<b>IG8362WSA</b>	
4-PLEX® surge suppression receptacles with lights, 80 joules, 6500A peak current.	Blue	-	<b>HBL420HS</b>
	Ivory	-	<b>HBL420HIS</b>
	Red	-	<b>HBL420HRS</b>


Note: See page Tech-10 for Tamper-Resistant and LED Power Indicators descriptions.



SNAP8362GYS



HBL8362ISA



HBL420HS

### 4-PLEX® Accessories

Description	Color	Catalog Number
4-PLEX Adapter Plates for 1- and 2-gang, and 4 in. (101.6) square device boxes.	Blue	<b>HBL4APBL</b>
	Ivory	<b>HBL4API</b>
	Red	<b>HBL4APR</b>
4-PLEX Portable Box, 4 in. (101.6) square box with cord grip. Accepts up to .66 in. (16.8) diameter cord.	Ivory	<b>HBL4PBI</b>

Note: 4-PLEX Box is not UL Listed.

UL2930 Listed



### UL2930 Health Care Outlet Assembly (HCOA)

Description	# of Outlets	Cord Length	Color	15 Amp	20 Amp
UL 2930 HCOA with L-N surge protection.	6	6'	White	<b>HBL6MG6</b>	<b>HBL6MG620</b>
	6	15'	White	<b>HBL6MG15</b>	<b>HBL6MG1520</b>
UL 2930 HCOA, Relocatable Power Tap (RPT).	6	6'	White	<b>HBL6MGRPT6</b>	<b>HBL6MGRPT620</b>
	6	15'	White	<b>HBL6MGRPT15</b>	<b>HBL6MGRPT1520</b>



HBL6MGRPT620

Listed to UL1449



### SpikeShield® Surge Protective Devices (SPD) with Tamper-Resistant Receptacles and Heavy Duty Plug

Description	# of Outlets	Cord Length	Color	15 Amp	20 Amp
Type 3 SPD, Heavy Duty metal housing.	6	6'	White	<b>HBL6HG6</b>	<b>HBL6HG620</b>
	6	15'	White	<b>HBL6HG15</b>	<b>HBL6HG1520</b>
UL Type 3 SPD, Heavy Duty metal housing with 2-port USB.	4	6'	White	<b>HBL6HGUSB6</b>	-




HBL6HGUSB6

Dimensions in Inches (mm)


## Circuit Guard®, Specification Grade Duplex Receptacles




Description	Color	Catalog Number	
Surge protection receptacles with light, 240 joules, 15kA peak current.	Blue	<b>HBL5260SA</b>	<b>HBL5360SA</b>
	Ivory	<b>HBL5260ISA</b>	<b>HBL5360ISA</b>
	Office White	<b>HBL5260WSA</b>	<b>HBL5360OWSA</b>
	White	<b>HBL5260WSA</b>	<b>HBL5360WSA</b>
Surge protection receptacles with light and alarm, 240 joules, 15kA peak current.	Almond	<b>HBL5262ALSA</b>	<b>HBL5362ALSA</b>
	Blue	<b>HBL5262SA</b>	<b>HBL5362SA</b>
	Gray	<b>HBL5262GYSA</b>	<b>HBL5362GYSA</b>
	Ivory	<b>HBL5262ISA</b>	<b>HBL5362ISA</b>
	Office White	<b>HBL5262OWSA</b>	<b>HBL5362OWSA</b>
	White	<b>HBL5262WSA</b>	<b>HBL5362WSA</b>
Isolated ground, surge protection receptacles with light and alarm, 240 joules, 15kA peak current.	Blue	<b>IG5262SA</b>	<b>IG5362SA</b>
	Gray	<b>IG5262GYSA</b>	<b>IG5362GYSA</b>
	Ivory	<b>IG5262ISA</b>	<b>IG5362ISA</b>
	Office White	<b>IG5262OWSA</b>	<b>IG5362OWSA</b>
	Orange	<b>IG5262OSA</b>	<b>IG5362OSA</b>
	White	<b>IG5262WSA</b>	<b>IG5362WSA</b>
4-PLEX® surge protection receptacles with lights, 80 joules, 6.5kA peak current.	Blue	<b>HBL415S</b>	<b>HBL420S</b>
	Ivory	<b>HBL415IS</b>	<b>HBL420IS</b>



**HBL5262GYSA**



**IG5362SA**



**HBL8362ISA**

## Circuit Guard®, Hospital Grade Duplex Receptacles


Description	Color	Catalog Number	
Surge protection receptacles with light and alarm, 240 joules, 15kA peak current.	Almond	<b>HBL8262ALSA</b>	<b>HBL8362ALSA</b>
	Blue	<b>HBL8262SA</b>	<b>HBL8362SA</b>
	Gray	<b>HBL8262GYSA</b>	<b>HBL8362GYSA</b>
	Ivory	<b>HBL8262ISA</b>	<b>HBL8362ISA</b>
	Red	<b>HBL8262RSA</b>	<b>HBL8362RSA</b>
	White	<b>HBL8262WSA</b>	<b>HBL8362WSA</b>
Isolated ground, surge protection receptacles with light and alarm, 240 joules, 15kA peak current.	Blue	<b>IG8262SA</b>	<b>IG8362SA</b>
	Gray	<b>IG8262GYSA</b>	<b>IG8362GYSA</b>
	Ivory	<b>IG8262ISA</b>	<b>IG8362ISA</b>
	Orange	<b>IG8262OSA</b>	<b>IG8362OSA</b>
	Red	<b>IG8262RSA</b>	<b>IG8362RSA</b>
	White	<b>IG8262WSA</b>	<b>IG8362WSA</b>
4-PLEX surge protection receptacles with lights, 80 joules, 6.5kA peak current.	Blue	—	<b>HBL420HS</b>
	Ivory	—	<b>HBL420HIS</b>
	Red	—	<b>HBL420HRS</b>

## 4-PLEX® Accessories


Description	Color	Catalog Number
4-PLEX adapter plates for 1- and 2-gang (4-PLEX mount directly to 4" (101.6) square device boxes).	Blue	<b>HBL4APBL</b>
	Ivory	<b>HBL4API</b>
	Red	<b>HBL4APR</b>
4-PLEX portable box. Portable 4" (101.6) square box with one cord grip. Accepts up to .66" (16.8) dia. cord.	Ivory	<b>HBL4PBI</b>

Note: 4-PLEX box is not UL Listed.

## Wallplates (Sold Separately)

Configuration	High-Impact Nylon			Plated Steel	Stainless Steel (S/S) Brass		
	Color	Standard	Mid-Size				
 1-Gang	Almond	<b>NP26AL</b>	<b>NPJ26AL</b>	Chrome Brass Plated	<b>SCH26</b> <b>SBP26</b>	Smooth S/S	<b>SS26</b>
	Blue	—	<b>NPJ26CBL*</b>			Smooth S/S	<b>SSJ26▲</b>
	Blue	—	<b>NPJ26BL</b>			Smooth	<b>SB26</b>
	Gray	<b>NP26GY</b>	<b>NPJ26GY</b>				
	Ivory	—	<b>NPJ26C*</b>				
	Ivory	<b>NP26I</b>	<b>NPJ26I</b>				
	Off. White	<b>NP26OW</b>	<b>NPJ26OW</b>				
	Orange	<b>NP26OIG**</b>	—				
	Red	<b>NP26R</b>	<b>NPJ26R</b>				
	White	<b>NP26W</b>	<b>NPJ26W</b>				

Note: \*Premarked "COMPUTER ONLY." Lettering is block 1/4" high.  
 \*\*Premarked "ISOLATED GROUND." Lettering is block 1/4" high.  
 ▲ Jumbo size plate.  
 See section O for additional wallplates.



**HBL415S**

Dimensions in Inches (mm)