



HBL11



HBL123SP


10A 250V AC 20A 125V AC Horsepower Rated 3/4 HP, 125-250V AC

Description	Terminal	Catalog Number
Single pole/ single throw.	Screw Spade	HBL11 HBL11SP
Single pole/ single throw momentary.	Screw Spade	HBL11M HBL11SPM
Single pole/ double throw.	Screw Spade	HBL12 HBL12SP
Single pole/ double throw 3-position center off.	Screw Spade	HBL123 HBL123SP
Single pole/ double throw 3-position center off momentary.	Screw Spade	HBL123MM HBL123SPMM

Note: All threaded stems 1/2 in.-32 thread.

10A 240V AC 15A 120V AC


Description	Terminal	Catalog Number
Single pole/ single throw.	Screw	HBL118



Note: 1/2 in.-32 thread.

4A 250V 8A 125V 10A 120V AC 1/3 HP 120V AC

Description	Terminal	Catalog Number
Single pole/ single throw.	#18 Std. AWG Copper Wire Leads 105° C Black.	HBL11WL



Note: 1/2 in.-32 thread, keyway .080 x .035.

Specifications

Impact Resistant Thermoplastic Body.

Fine Silver Contacts.

Knurled Nut, Hex Nut And Strap All Nickel Plated.

Keyed Brass Bushing Nickel Plated.

Brass Toggle Nickel Plated.

Choice of Terminal Design: .250 in. (6.3) Male Tab Spade Type or 6/32 Screw Type.

UL Recognized.

Dimensions in Inches (mm)