

| | Volume | | Product Code |
|--|----------|--------|--------------|
| | imperial | metric | |

IPEX 71 ABS CEMENT

YELLOW ■

LOW VOC, 3 Year Shelf Life

Meets ASTM D2235 for use with ABS pipe. NSF listed to CSA B181.1 for ABS DWV pipe and fittings.

Medium-bodied, fast setting ABS cement for all classes and schedules through 150 mm (6") interference fit.



| | | |
|-------|--------|--------|
| quart | 946 ml | 074180 |
|-------|--------|--------|

IPEX 90 MULTI-PURPOSE SOLVENT CEMENT

CLEAR

LOW VOC, 2 Year Shelf Life

Medium-bodied, fast setting cement for all PVC and CPVC pipe and fittings through 150 mm (6") interference fit, Sch. 80 through 100 mm (4").

When joining similar materials (PVC to PVC, etc.) use cement specifically recommended for that purpose.



| | | |
|------|--------|--------|
| pint | 473 ml | 074402 |
|------|--------|--------|

| | Volume | | Product Code |
|--|----------|--------|--------------|
| | imperial | metric | |

IPEX 95 FLEX PVC CEMENT

CLEAR

Low VOC, 3 Year Shelf Life

Meets ASTM D2564. NSF and IAPMO listed for potable water and sewer pipe.

Medium-bodied, fast setting, for bonding flex/flex and flex/rigid PVC pipe and fittings through 150 mm (6") diameter interference fit, Sch. 80 through 75 mm (3") only. Excellent product for flex/rigid applications. It has an elastomer in the formulation which allows a more flexible joint.



| | | |
|----------|--------|--------|
| 1/4 pint | 118 ml | 074440 |
| 1/2 pint | 236 ml | 074163 |
| quart | 946 ml | 074412 |

IPEX 96 ABS/PVC CEMENT

WHITE

3 Year Shelf Life

CSA certified for nonpressure ABS/PVC systems only. Meets ASTM D3138.

Regular-bodied, fast setting, FOR TRANSITION JOINTS ONLY IN NON-PRESSURE SYSTEMS. Pipe sizes through 150 mm (6") interference fit. Not for Sch. 80. Suitability of IPEX 96 should be verified for specific ABS/PVC materials.



| | | |
|------|--------|--------|
| pint | 473 ml | 074461 |
|------|--------|--------|