

MJ GREY COUPLINGS

8" - 12" (200mm - 300mm)

MJ GREY™ DWV

IPEX is proud to bring more jobsite relief to your crew by introducing MJ Grey™ Mechanical Couplings to the "System" family.

Certified to CSA B602 and listed to CAN/ULC S102.2 our MJ Grey mechanical couplings are available in 8", 10" and 12" configurations for System 15 or System XFR. On large diameter joints, mechanical couplings are a great alternative to solvent cementing when working in cold weather conditions or from heights in a scissor lift or bucket. Relief is also available when you need to make an installation adjustment as our MJ's can be adjusted in-field as required.

ADVANTAGES

- 1 **Used with System 15 and or System XFR**
- 2 **Sizes 8" to 12"**
- 3 **Designed Specifically for PVC Diameters**
- 4 **Stainless Steel Band with Rubber Sleeve**
Colour coded grey to match the pipe
- 5 **Certified to CSA B602**
- 6 **Listed to ULC 102.2/10**
For the Flame Spread Rating / Smoke Developed Classification limits of 25/50

APPLICATIONS

Drain Waste and Vent Piping in:

- Commercial
- Industrial
- Residential
- Above ground or underground

STANDARDS



CSA B181.2
CAN/ULC S102.2




Test Results

Normal testing procedures for System 15 or System XFR may be employed if using MJ Grey couplings. Maximum water or air test pressure shall be 10 feet of head or 4.3 psi for all sizes.

Proper safety precautions and protective equipment should be employed during all testing procedures.

Component	Flame Spread Rating	Smoke-Developed Classification
MJ Grey™		
Couplings	≤ 25	≤ 50

Dimensions




Coupling Size (in)	Length (L) (in)	N # of Clamps
8	6.0	6
10	6.0	6
12	6.0	6

PRODUCT SELECTION CHART - MJ GREY


Dimension	Product Code	
	inches	mm

MJ Coupling H x H



8	200	094053
10	250	094054
12	300	094055

T-Handle Torque Wrench 80 in-lb



5/16" socket	094139
--------------	--------

SHORT FORM SPECIFICATIONS

MJ GREY™ COUPLINGS

MJ Grey couplings are a mechanical joint assembly suitable for use on IPEX System 15 or System XFR DWV piping. These couplings come in a range of sizes from 8" to 12" in diameter. They are designed specifically for PVC pipe and are certified to CSA B602, as well as listed to ULC 102.2/10, while exhibiting a flame smoke rating of 25/50.

i DID YOU KNOW?

MJ GREY — The MJ Grey coupling may be used to accommodate small changes in alignment up to 1.5° in any direction.

