






## table of contents

# Convenience Outlets and Receptacles

<ul style="list-style-type: none"> <li>Snap-In Convenience Outlets           <ul style="list-style-type: none"> <li>2-Pole, 3-Wire Grounding . . . . . <b>K2-K7</b></li> <li>Grounding Outlet with Grounding Lead . . . . . <b>K2-K4, K6-K7</b></li> <li>Grounding Plug . . . . . <b>K5</b></li> <li>Grounding Outlet with Solder Lug or Screw Terminal Ground. . . . <b>K6-K7</b></li> </ul> </li> <li>Outlet with Back-Strap Mounting. . . . . <b>K8</b></li> <li>Flat Head Convenience Outlets . . . . . <b>K8</b></li> <li>Straight Blade Receptacles, Box Mount . . . . . <b>K9-K11</b></li> <li>DIN-Rail Mount Receptacles. . . . . <b>K12</b></li> </ul>
---

### Quick Guide to Snap-In Outlets and Plugs

Panel Cutout Dimensions	Description	Rating/NEMA	Cat. No.	UL	CSA	NOM	Page No.
.953 x .953 (24.21 X 24.21)	Grounding outlet with grounding lead	15A-125V 5-15R 	1374 (-001 to -204)	✓	✓	✓	K2-K4
			1374 (-500)	✓	✓	✓	K6-K7
.953 x .953 (24.21 x 24.21)	Grounding plug	15A-125V 5-15P 	1373	✓	✓	—	K5
.953 x .953 (24.21 x 24.21)	Grounding outlet with solder lug or screw terminal ground	15A-125V 5-15R 	1374 (-625 to -675)	*	✓	✓	K6-K7
			1374 (-725 to -775)	✓	✓	✓	K6-K7
.969 x .516 (24.59 x 13.11)	Outlets	15A-125V Polarized 1-15R 	306	✓	✓	✓	K8
			1306	✓	✓	✓	K8
			298	*	—	✓	K8

\*UL Recognized Component 

NOTE: Dimensions in parentheses are in millimeters. All other dimensions are in inches.



306

## Back-Strap Mounting

**Cat. No. 306:** For surface mounting, adapted for use with flat-type plugs. Round plugs may be used when properly protected.

**Leads:** Standard leads are No. 14 AWG 105°C AWM-TEW plastic insulated wire, 6" long, stripped 3/4", internally soldered. Other leads available on inquiry.

**Body:** Plastic, black or white.

**Clip:** Steel with corrosion-resistant finish.

**Standard pack:** bulk

- 15A-125V Polarized
- UL Listed E-13399
- CSA Certified LR-2781
- NOM Certified 057
- NEMA 1-15R

Cat. No.	Description	Leads
306	Black	14 ga.
306-00W	White	14 ga.



1306

## Flat-Head Convenience Outlet

**Cat. No. 1306:** For snap-in mounting applications where a grounding wire is not required.

**Leads:** Standard leads are No. 14 AWG 105°C AWM-TEW plastic insulated wire, 6" long, stripped 3/4". Other leads available on inquiry, including straight or 90° orientation.

**Body:** Plastic, black or white.

**Clip:** Plastic serrated clip with integral back cover, metal clip is optional.

**Cat. No. 298:** Same specifications as 1306, but with No. 18 AWG leads.

**Cat. No. 298-300:** 2-pole, 3-wire grounding with No. 18 AWG leads and metal clip.

**Standard pack:** bulk

- 15A-125V Polarized
- UL Listed E-13399 (Cat. No. 1306)
- UL Recognized Component (Cat. No. 298)
- CSA Certified LR-2781 (Cat. No. 1306)
- NOM Certified 057
- NEMA 1-15R



298

Cat. No.	Description	Leads
1306	Black	14 ga.
1306-00W	White	14 ga.
298	Black	18 ga.
298-00W	White	18 ga.
298-300	Black	18 ga.

