

Auxiliary Contacts for Safety Disconnect Switches

- Leviton Disconnect Switches automatically ship with one factory installed auxiliary contact, normally open.
- A second auxiliary contact may be added. Select from the table below.



DEVICE	CATALOG NO.	DESCRIPTION
For ALL non-fused and fused disconnect switches	AUXNO	Normally open contact, 10 Amp, early break type
	AUXNC-NF	Normally closed contact, 10 Amp, early break type
For ALL fused disconnect switches	AUXNC-F	Normally closed contact, 10 Amp, early break type

Wallplates for Standard Toggle and Locking Switches

SINGLE-GANG

TWO-GANG

	Color	Cat. No.	Material		Color	Cat. No.	Material
	Ivory	80701-I	Nylon		Ivory	80709-I	Nylon
	Black	80701-E	Nylon		Black	80709-E	Nylon
	Gray	80701-G	Nylon		Gray	80709-G	Nylon
	White	80701-W	Nylon		White	80709-W	Nylon
	Brown	80701	Nylon		Brown	80709	Nylon
	Almond	80701-A	Nylon		Almond	80709-A	Nylon
	Brushed Stainless	84001-40	302 Stainless Steel		Brushed Stainless	84009-40	302 Stainless Steel

Key Locking Switch Accessories

302 STAINLESS STEEL WALLPLATE COMES WITH TAMPER-RESISTANT SCREWS & SPANNER TOOL	
	84071-40
	84072-40
	84073-40



ADAPTER EXTENDS SHALLOW WALLBOX, USE WITH STAINLESS STEEL WALLPLATE, CATALOG NO. 84071-40	
WALLBOX ADAPTER	
COLOR	CATALOG NO.
Brown	6197
Ivory	6197-I
White	6197-W