

30A, 50A and 60A Devices

Industrial Grade Power Devices

Built from durable thermoplastic, Leviton power receptacles — in flush mount, surface mount and panel mount versions — come equipped with heavy-gauge, double-wire copper alloy contacts. To ensure correct and speedy wiring, terminals have ID markings. Flush mount receptacles fit Leviton's wide range of 2.15"-diameter wallplates and mounting hardware is included. Angle plugs are made of tough, heavy-duty nylon for a long dependable service life.

279-PM, 5054 and 279



Features and Benefits

- Heavy-gauge, double-wipe copper alloy contacts
- Easy-to-wire terminals accept up to #4 AWG conductors
- Terminals marked for easy identification and fast wiring
- All mounting hardware included
- Flush-mount devices fit single or two-gang outlet boxes
- Surface-mount devices are commercial grade and have concentric knockouts for 3/4" and 1" conduit and adjustable cord clamp for back and bottom entrance of cable

Angle Plugs

- Rugged cord clamp for secure cable grip accommodates cord diameters from .625" to 1.375" and does not tear conductor jacket
- Made of tough, heavy-duty nylon for long service life
- Devices feature heavy-sectioned dead-front right-angle
- Pressure-clamp terminal design
- Terminals accept up to #4 AWG stranded conductors
- Four-way positioning front module
- Solid brass blades for maximum conductivity

30A, 50A, 60A | Power Devices

30A, 50A and 60A Industrial Grade Power Devices

30A Single Receptacles and Plugs

Rating	30A-125V	30A-125V	
NEMA			
	5-30P	5-30R	
Description	Cat. No.	Cat. No.	Wallplate Information
Flush Mount Receptacle	—	5371	Fits all wallplates with 2.15" diameter center hole
Flush Mount Receptacle, Isolated Ground	—	5371-IG	Fits all wallplates with 2.15" diameter center hole
Angle Plug	9530-P	—	



9530-P

Rating	30A-125V	30A-125V	
NEMA			
	TT-30P	TT-30R	
Description	Cat. No.	Cat. No.	Wallplate Information
Flush Mount Receptacle for Recreational Vehicles	—	7313	Fits all wallplates with 2.15" diameter center hole
Angle Plug	830-T	—	



830-T

Rating	30A-250V	30A-250V	
NEMA			
	6-30P	6-30R	
Description	Cat. No.	Cat. No.	Wallplate Information
Flush Mount Receptacle	—	5372	Fits all wallplates with 2.15" diameter center hole
Flush Mount Receptacle, Isolated Ground	—	5372-IG	Fits all wallplates with 2.15" diameter center hole
Surface Mount Receptacle	—	5376	Fits all wallplates with 2.15" diameter center hole
Angle Plug	9630-P	—	



5376

Rating	30A-277V	30A-277V	
NEMA			
	7-30P	7-30R	
Description	Cat. No.	Cat. No.	Wallplate Information
Flush Mount Receptacle	—	9730-A	Fits all wallplates with 2.15" diameter center hole
Angle Plug	9730-P	—	



9730-P