

15A | Watertight

Wetguard® Watertight Locking Plugs, Connectors, Inlets, Outlets and Receptacles

Features and Benefits

- Corrosion-resistant electroless nickel-coated brass blades, contacts, terminal screws and wiring clamps, and stainless steel assembly screws make these devices ideal for use in wet and corrosive environments
- EPTR rubber part provides outstanding resistance to wet and damp environments, extreme temperature variations, water, acids, alkalis, grease, oils and many automotive and industrial lubricants and solvents
- Plug and connector husk is molded to a bondable nylon body, providing a device that withstands physical abuse
- Interlocking “tongue and groove” construction seals out water, moisture and dirt when plugs are mated with connectors
- Multi-point sealing system utilizes nut, strain relief washer and rubber bushing to form a watertight cord grip seal
- Non-magnetic stainless steel fast-threading assembly screws won't interfere with sensitive equipment
- Connector “hood” closure cap seals device when not in use
- Most devices also available in black. Check for availability
- Devices are UL and CSA listed and have enclosure ratings of NEMA 4, 4X, 12 and IEC IP66, IP67 when mated or with cover closed
- Backed by a lifetime warranty

Wetguard® Locking Plugs, Connectors, Inlets, Outlets and Receptacles

15A Wetguard® Locking Devices

| Rating | 15A-125V | 15A-125V | 15A-250V | 15A-277V | |
|----------------------------|----------|----------|----------|----------|----------|
| Configuration | 2P 2W | 2P 3W | 2P 3W | 2P 3W | |
| NEMA | L1-15 | L5-15 | L6-15 | L7-15 | |
| Description | Color | Cat. No. | Cat. No. | Cat. No. | Cat. No. |
| Plug | Yellow | 24W04 | 24W47* | 24W49 | 24W34 |
| Plug Cap | | 14W* | 14W* | 14W* | 14W* |
| Connector | | 25W04 | 25W47* | 25W49 | 25W34 |
| Connector Cap | | 50W50* | 50W50* | 50W50* | 50W50* |
| Single Outlet | | 95W04-S | 95W47-S | 95W49-S | 95W34-S |
| Duplex Outlet | | 85W04-D | 85W47-D | 85W49-D | 85W34-D |
| Single Inlet | | 64W04 | 64W47 | 64W49 | 64W34 |
| Connector for Single Inlet | | 74W04-C | 74W47-C | 74W49-C | 74W34-C |
| Single Receptacle | | — | 47CM-10 | 45CM-60 | 47CM-60 |
| Receptacle Cover w/Gasket | | — | 60W03* | 60W03* | 60W03* |



24W04



50W50

NEMA configuration diagrams represent plug blade configuration.
 *Available in black. To order, add “-B” suffix to catalog number

SPOTLIGHT

Wetguard® Watertight Wiring Devices

The Wetguard® line consists of a comprehensive array of plugs, connectors, inlets, outlets, covers and an industry exclusive FD Box system that allows mounting of single-gang devices in multi-gang configurations. Visit www.leviton.com/wetguard for more information.



20A AND 20/10A | Watertight

Continued from previous page

Wetguard® Locking Plugs, Connectors, Inlets, Outlets and Receptacles

| 20A and 20/10A Wetguard® Locking Devices | | | | | | |
|--|--------|--------------|---------------------|---------------------|---------------------|----------------------|
| Rating | | 20A-125/250V | 20A-3Ø 250V | 20A-3Ø 480V | 20A-3ØY 120/208V | |
| Configuration | | 3P 4W | 3P 4W | 3P 4W | 4P 4W | |
| NEMA | | | | | | |
| | | L14-20 | L15-20 | L16-20 | Non-NEMA | |
| Description | Color | Cat. No. | Cat. No. | Cat. No. | Cat. No. | |
| Plug | Yellow | 26W74 | 26W75* | 26W76* | 26W09 | |
| Plug Cap | | 26W* | 26W* | 26W* | 26W* | |
| Connector | | 27W74 | 27W75* | 27W76* | 27W09 | |
| Connector Cap | | 50W52* | 50W52* | 50W52* | 50W52* | |
| Single Outlet | | 97W74-S | 97W75-S | 97W76-S | 97W09-S | |
| Duplex Outlet | | — | — | — | — | |
| Single Inlet | | 66W74 | 66W75 | 66W76 | 66W09 | |
| Connector for Single Inlet | | 76W74-C | 76W75-C | 76W76-C | 76W09-C | |
| Single Receptacle | | 24CM-10 | 24CM-20 | 24CM-30 | 7410-B | |
| Receptacle Cover w/Gasket | | 60W04* | 60W04* | 60W04* | 60W04* | |
| Rating | | | 20A-3ØY 120/208V | 20A-3ØY 277/480V | 20A-3ØY 347/600V | 20A-250V 10A-600V |
| Configuration | | | 4P 5W | 4P 5W | 4P 5W | 4P 5W |
| NEMA | | | | | | |
| | | L21-20 | L22-20 | L23-20 | Non-NEMA | |
| Description | Color | Cat. No. | Cat. No. | Cat. No. | Cat. No. | |
| Plug | Yellow | 26W81* | 26W82 | 26W83 | 26W10 | |
| Plug Cap | | 26W* | 26W* | 26W* | 26W* | |
| Connector | | 27W81* | 27W82 | 27W83 | 27W10 | |
| Connector Cap | | 50W52* | 50W52* | 50W52* | 50W52* | |
| Single Outlet | | 97W81-S | 97W82-S | 97W83-S | 97W10-S | |
| Duplex Outlet | | — | — | — | — | |
| Single Inlet | | 66W81 | 66W82 | 66W83 | 66W10 | |
| Connector for Single Inlet | | 76W81-C | 76W82-C | 76W83-C | 76W10-C | |
| Single Receptacle | | 2510 | 2520 | 2530 | — | |
| Receptacle Cover w/Gasket | | 60W04* | 60W04* | 60W04* | 60W04* | |

NEMA configuration diagrams represent plug blade configuration.
*Available in black. To order, add "-B" suffix to catalog number



26W74



66W76



26W



27W81



Related Products

See section H for more information on the entire line of watertight wiring devices.

Locking Plugs, Connectors, Inlets, Outlets and Receptacles

Product Overview

Features and Benefits

- Corrosion-resistant electroless nickel-coated brass blades, contacts, terminal screws and wiring clamps, and stainless steel assembly screws make these devices ideal for use in wet and corrosive environments
- EPTR rubber part provides outstanding resistance to wet and damp environments, extreme temperature variations, water, acids, alkalis, grease, oils and many automotive and industrial lubricants and solvents
- Plug and connector husk is molded to a bondable nylon body, providing a device that withstands physical abuse
- Interlocking “tongue and groove” construction seals out water, moisture and dirt when plugs are mated with connectors
- Multi-point sealing system utilizes nut, strain relief washer and rubber bushing to form a watertight cord grip seal
- Non-magnetic stainless steel fast-threading assembly screws won't interfere with sensitive equipment
- Connector “hood” closure cap seals device when not in use
- Most devices also available in black. Check for availability
- Devices are UL and CSA listed and have enclosure ratings of NEMA 4, 4X, 12 and IEC IP66, IP67 when mated or with cover closed
- Backed by a lifetime warranty

Wetguard® Watertight Locking Devices



Plug



Plug Cap



Connector



Connector Cap



Single Outlet



Duplex Outlet



Single Inlet



Connector Mates w/Inlet



Single Receptacle



Receptacle Cover

WETGUARD® LOCKING DEVICES | 15A | 15/10A and 20A

Locking Devices – 15A

| 15A Wetguard® Locking Devices | | | | | | | | | | | | |
|-------------------------------|------|--------------------|----------|----------|-----------|---------------|---------------|---------------|--------------|----------------------------|-------------------|---------------------------|
| | | | Cat. No. | | | | | | | | | |
| Amp | Volt | NEMA Configuration | Plug | Plug Cap | Connector | Connector Cap | Single Outlet | Duplex Outlet | Single Inlet | Connector for Single Inlet | Single Receptacle | Receptacle Cover w/Gasket |
| 2-Pole, 2-Wire | | | | | | | | | | | | |
| 15 | 125 | L1-15 | 24W04 | 14W* | 25W04 | 50W50* | 95W04-S | 85W04-D | 64W04 | 74W04-C | — | — |
| 2-Pole, 3-Wire | | | | | | | | | | | | |
| 15 | 125 | L5-15 | 24W47* | 14W* | 25W47* | 50W50* | 95W47-S | 85W47-D | 64W47 | 74W47-C | 47CM-10 | 60W03* |
| 15 | 250 | L6-15 | 24W49 | 14W* | 25W49 | 50W50* | 95W49-S | 85W49-D | 64W49 | 74W49-C | 45CM-60 | 60W03* |
| 15 | 277 | L7-15 | 24W34 | 14W* | 25W34 | 50W50* | 95W34-S | 85W34-D | 64W34 | 74W34-C | 47CM-60 | 60W03* |

NEMA configuration diagrams represent plug blade configuration.
 *Available in black. To order, add "-B" suffix to catalog number

Locking Devices – 15/10A and 20A

| 15/10A and 20A Wetguard® Locking Devices | | | | | | | | | | | | |
|--|------------|--------------------|----------|----------|-----------|---------------|---------------|---------------|--------------|----------------------------|-------------------|---------------------------|
| | | | Cat. No. | | | | | | | | | |
| Amp | Volt | NEMA Configuration | Plug | Plug Cap | Connector | Connector Cap | Single Outlet | Duplex Outlet | Single Inlet | Connector for Single Inlet | Single Receptacle | Receptacle Cover w/Gasket |
| 3-Pole, 3-Wire | | | | | | | | | | | | |
| 15 10 | 125 250 | Non-NEMA | 24W07 | 14W* | 25W07 | 50W50* | 95W07-S | 85W07-D | 64W07 | 74W07-C | — | — |
| 2-Pole, 2-Wire | | | | | | | | | | | | |
| 20 | 250 | L2-20 | 26W07 | 26W* | 27W07 | 50W50* | 97W07-S | 87W07-D | 66W07 | 76W07-C | — | — |

NEMA configuration diagrams represent plug blade configuration.
 *Available in black. To order, add "-B" suffix to catalog number

SPOTLIGHT

Wetguard® Watertight

The Wetguard® line consists of a comprehensive array of plugs, connectors, inlets, outlets, covers and an industry exclusive FD Box system that allows mounting of single-gang devices in multi-gang configurations. Visit www.leviton.com/wetguard for more information.



WETGUARD® LOCKING DEVICES | 20A and 20/10A
Locking Devices — 20A and 20/10A

| 20A and 20/10A Wetguard® Locking Devices | | | | | | | | | | | | | |
|--|----------------|--------------------|----------|----------|-----------|---------------|---------------|---------------|--------------|----------------------------|-------------------|---------------------------|--|
| | | | Cat. No. | | | | | | | | | | |
| Amp | Volt | NEMA Configuration | Plug | Plug Cap | Connector | Connector Cap | Single Outlet | Duplex Outlet | Single Inlet | Connector for Single Inlet | Single Receptacle | Receptacle Cover w/Gasket | |
| 2-Pole, 3-Wire | | | | | | | | | | | | | |
| 20 | 125 | L5-20 | 26W47* | 26W* | 27W47* | 50W52* | 97W47-S | — | 66W47 | 76W47-C | 23CM-10 | 60W04* | |
| 20 | 250 | L6-20 | 26W48* | 26W* | 27W48* | 50W52* | 97W48-S | — | 66W48 | 76W48-C | 23CM-20 | 60W04* | |
| 20 | 277 | L7-20 | 26W49 | 26W* | 27W49 | 50W52* | 97W49-S | — | 66W49 | 76W49-C | 23CM-30 | 60W04* | |
| 20 | 347 | L24-20 | 22W07 | 26W* | 23W07 | 50W52* | 93W07-S | — | 68W29 | 78W29-C | — | — | |
| 3-Pole, 3-Wire | | | | | | | | | | | | | |
| 20 | 125/ 250 | Non-NEMA | 26W08 | 26W* | 27W08 | 50W52* | 97W08-S | — | 66W08 | 76W08-C | 7310-B | 60W04* | |
| 20 | 250 | Non-NEMA | 26W08-G | 26W* | 27W08-G | 50W52* | — | — | — | — | — | — | |
| 10 | 600 | Non-NEMA | — | — | — | — | — | — | — | — | — | — | |
| 3-Pole, 4-Wire | | | | | | | | | | | | | |
| 20 | 125/ 250 | L14-20 | 26W74 | 26W* | 27W74 | 50W52* | 97W74-S | — | 66W74 | 76W74-C | 24CM-10 | 60W04* | |
| 20 | 3Ø 250 | L15-20 | 26W75* | 26W* | 27W75* | 50W52* | 97W75-S | — | 66W75 | 76W75-C | 24CM-20 | 60W04* | |
| 20 | 3Ø 480 | L16-20 | 26W76* | 26W* | 27W76* | 50W52* | 97W76-S | — | 66W76 | 76W76-C | 24CM-30 | 60W04* | |
| 4-Pole, 4-Wire | | | | | | | | | | | | | |
| 20 | 3ØY 120/208 | Non-NEMA | 26W09 | 26W* | 27W09 | 50W52* | 97W09-S | — | 66W09 | 76W09-C | 7410-B | 60W04* | |
| 4-Pole, 5-Wire | | | | | | | | | | | | | |
| 20 | 3ØY 120/208 | L21-20 | 26W81* | 26W* | 27W81* | 50W52* | 97W81-S | — | 66W81 | 76W81-C | 2510 | 60W04* | |
| 20 | 3ØY 277/480 | L22-20 | 26W82 | 26W* | 27W82 | 50W52* | 97W82-S | — | 66W82 | 76W82-C | 2520 | 60W04* | |
| 20 | 3ØY 347/600 | L23-20 | 26W83 | 26W* | 27W83 | 50W52* | 97W83-S | — | 66W83 | 76W83-C | 2530 | 60W04* | |
| 20 | 250 | Non-NEMA | 26W10 | 26W* | 27W10 | 50W52* | 97W10-S | — | 66W10 | 76W10-C | — | 60W04* | |
| 10 | 600 | Non-NEMA | — | — | — | — | — | — | — | — | — | — | |

NEMA configuration diagrams represent plug blade configuration.
 *Available in black. To order, add “-B” suffix to catalog number

WETGUARD® LOCKING DEVICES | 30A

Locking Devices — 30A

| 30A Wetguard® Locking Devices | | | | | | | | | | | | |
|-------------------------------|-------------|--------------------|----------|----------|-----------|---------------|---------------|---------------|--------------|-------------------------|-------------------|---------------------------|
| | | | Cat. No. | | | | | | | | | |
| Amp | Volt | NEMA Configuration | Plug | Plug Cap | Connector | Connector Cap | Single Outlet | Duplex Outlet | Single Inlet | Connector Mates w/Inlet | Single Receptacle | Receptacle Cover w/Gasket |
| 2-Pole, 3-Wire | | | | | | | | | | | | |
| 30 | 125 | L5-30 | 28W47* | 28W* | 29W47* | 50W54* | 99W47-S | — | 68W47 | 78W47-C | 26CM-10 | 60W05* |
| 30 | 250 | L6-30 | 28W48* | 28W* | 29W48* | 50W54* | 99W48-S | — | 68W48 | 78W48-C | 26CM-20 | 60W05* |
| 30 | 277 | L7-30 | 28W49 | 28W* | 29W49 | 50W54* | 99W49-S | — | 68W49 | 78W49-C | 2630 | 60W05* |
| 3-Pole, 3-Wire | | | | | | | | | | | | |
| 30 | 125/250 | Non-NEMA | 28W08 | 28W* | 29W08 | 50W54* | 99W08-S | — | 68W08 | 78W08-C | 3330 | 60W05* |
| 3-Pole, 4-Wire | | | | | | | | | | | | |
| 30 | 125/250 | L14-30 | 28W74 | 28W* | 29W74 | 50W54* | 99W74-S | — | 68W74 | 78W74-C | 27CM-10 | 60W05* |
| 30 | 3Ø 250 | L15-30 | 28W75 | 28W* | 29W75 | 50W54* | 99W75-S | — | 68W75 | 78W75-C | 27CM-20 | 60W05* |
| 30 | 3Ø 480 | L16-30 | 28W76* | 28W* | 29W76* | 50W54* | 99W76-S | — | 68W76 | 78W76-C | 2730 | 60W05* |
| 30 | 3ØY 600 | L17-30 | 28W77 | 28W* | 29W77 | 50W54* | 99W77-S | — | 68W77 | 78W77-C | 2740 | 60W05* |
| 4-Pole, 4-Wire | | | | | | | | | | | | |
| 30 | 3ØY 120/208 | Non-NEMA | 28W09 | 28W* | 29W09 | 50W54* | 99W09-S | — | 68W09 | 78W09-C | 3430 | 60W05* |
| 4-Pole, 5-Wire | | | | | | | | | | | | |
| 30 | 3ØY 120/208 | L21-30 | 28W81 | 28W* | 29W81 | 50W54* | 99W81-S | — | 68W81 | 78W81-C | 2810 | 60W05* |
| 30 | 3ØY 277/480 | L22-30 | 28W82 | 28W* | 29W82 | 50W54* | 99W82-S | — | 68W82 | 78W82-C | 2820 | 60W05* |
| 30 | 3ØY 347/600 | L23-30 | 28W83 | 28W* | 29W83 | 50W54* | 99W83-S | — | 68W83 | 78W83-C | 2830 | 60W05* |

NEMA configuration diagrams represent plug blade configuration.
 *Available in black. To order, add "-B" suffix to catalog number

SPOTLIGHT Wetguard® Watertight

The Wetguard® line consists of a comprehensive array of plugs, connectors, inlets, outlets, covers and an industry exclusive FD Box system that allows mounting of single-gang devices in multi-gang configurations. Visit www.leviton.com/wetguard for more information.



Switch Cover, Plate and Replacement Covers

| Switch Covers, Plate and Replacement Covers | | |
|---|--------|--|
| Cat. No. | Color | Description |
| COVER-S | Yellow | Single Gang Switch Cover and Gasket for any 15A-40A Toggle Switch, including Leviton |
| COVER-GS | Gray | Manual Motor Starters |
| WTCVD* | Yellow | Wetguard® Replacement Cover and Gasket for Wetguard® Duplex Outlets Only |
| WTCVS-15 | Yellow | Wetguard® Replacement Cover and Gasket for 15A and 20A Straight and 15A Locking Single Inlets and Outlets |
| WTCVS-20 | Yellow | Wetguard® Replacement Cover and Gasket for all 20A Locking Single Inlets and Outlets |
| WTCVS-30 | Yellow | Wetguard® Replacement Cover and Gasket for all 30A Locking Single Inlets and Outlets |
| WP459 | Yellow | Wetguard® Blank Plate and Gasket |
| 60W03 | Yellow | Wetguard® Cover and Gasket for 15A and 20A Straight Blade and 15A Locking Box Mount Single Flush Receptacles |
| 60W04 | Yellow | Wetguard® Cover and Gasket for 20A Locking Box Mount Single Flush Receptacles |
| 60W05 | Yellow | Wetguard® Cover and Gasket for 30A Locking Box Mount Single Flush Receptacles |

*Not for use with standard duplex devices



COVER-GS



WTCVS-15



60W03



WP459



WTCVD

SPOTLIGHT

Wetguard® Watertight

The Wetguard® line consists of a comprehensive array of plugs, connectors, inlets, outlets, covers and an industry exclusive FD Box system that allows mounting of single-gang devices in multi-gang configurations. Visit www.leviton.com/wetguard for more information.

