

# Conduit and Accessories

## Support Conduit on Walls and Structures

### Pipe Straps

- Available in malleable iron/stamped steel with nominal 0.015 in (15 mils) PVC coating in your choice of blue, white or grey
- Choose one- or two-hole versions
- Sized to allow for the extra thickness of the PVC coating



Two-Hole PVC-Coated Pipe Strap


One-Hole PVC-Coated Pipe Strap

### PVC-Coated Pipe Straps

Cat. No.		Pipe Size in. (mm)
One-Hole Malleable Iron	Two-Hole Stamped Steel	
1HS1/2C- <u>  </u>	2HS1/2C- <u>  </u>	1/2 (16)
1HS3/4C- <u>  </u>	2HS3/4C- <u>  </u>	3/4 (21)
1HS1C- <u>  </u>	2HS1C- <u>  </u>	1 (27)
1HS1-1/4C- <u>  </u>	2HS1-1/4C- <u>  </u>	1-1/4 (35)
1HS1-1/2C- <u>  </u>	2HS1-1/2C- <u>  </u>	1-1/2 (41)

Metric size designator (ANSI C80.1-1994).

## Pipe Spacers – PVC Coated



Corrosion resistant PVC coated malleable iron. Pre-mountable, stackable to eliminate offsetting.

Spacers can be stacked for offsets on wall or into outlet box. Prevents conduit rusting from wall condensation. Eliminates offsetting of conduit.

Cat. No.	Conduit Size (in.)	Screw Size	Dimensions (in.)	
			A	B
1350CR	1/2 – 3/4 – 1	#7	3	7/8
1351CR	1/4 – 1/2 – 2	#12	5	3/8
1352CR	2-1/2 – 3	#12	6-9/16	1-3/4
1353CR	3-1/2 – 4	#14	7-9/16	2
1354CR	4-1/2 – 5 – 6	#16	10-9/16	2-9/16

UL not applicable.  
Conforms to CEC Rule 12-012 (5)