









Selection and ordering data

Version	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*/P. unit	PG
 <p>8WA1808</p> <p>End retainers, with screw fixing</p> <ul style="list-style-type: none"> • Mounting width 10 mm • Suitable for 8WA1806 end labeling plate or 8WA8826-0A terminal strip identification label or 3TX4 210-0H device label or four 8WA88.. labels 		8WA1808		1	50 units	041
 <p>8WA1805</p> <p>End retainers, steel</p> <ul style="list-style-type: none"> • Mounting width 10.3 mm • Suitable for 8WA1806 end labeling plate <p>Note</p> <p>An 8WA1820 barrier must be inserted if using end retainers against an 8WA189.. connection bar (size 2.5).</p>		8WA1805		1	50 units	041
 <p>5ST1141</p> <p>Standard mounting rails</p> <p>Versions</p> <ul style="list-style-type: none"> • With holes <ul style="list-style-type: none"> - EN 50 022-35 × 7.5 - 2 m long, 1 mm thick - Steel, sendzimir-galvanized • Non-perforated • Non-perforated, copper <ul style="list-style-type: none"> - EN 50022-35 × 15 - 2 m long, 2.3 mm thick • Non-perforated, steel, galvanized, chromated <ul style="list-style-type: none"> - Similar to EN 50022-35 × 15 - 2 m long, 1.5 mm thick 		5ST1145		1	20 units	020
		5ST1141		1	20 units	020
		8WA7551		1	1 unit	041
		5ST1142		1	10 units	020
 <p>8WA1868</p> <p>Test plugs</p> <ul style="list-style-type: none"> • For 8WA1 and 8WA2 terminals with 2.3 mm Ø hole or 8WA1854, 8WA1884 test sockets • Uninterrupted current 10 A <p>Versions</p> <ul style="list-style-type: none"> • Red 		8WA1868		1	10 units	041
 <p>8WA1884</p> <p>Test sockets</p> <ul style="list-style-type: none"> • Ø 2.3 mm • With matching spacer sleeve for connection bars, terminal sizes 2.5 and 4 mm², two-tier terminals, rear level, terminal size 6 mm² • Uninterrupted current 10 A <p>Versions</p> <ul style="list-style-type: none"> • Test sockets • Spacer sleeves <p>Note</p> <p>The test socket must be used with a spacer sleeve.</p>		8WA1884 8WA1822-7VH11		1	100 units	041
				1	100 units	041
 <p>8WA1871</p> <p>Reduction plugs</p> <ul style="list-style-type: none"> • For 8WA1 and 8WA2 terminals with 2.3 mm Ø hole or 8WA1854, 8WA1884 test sockets • Uninterrupted current 10 A • With 4 mm Ø hole 		8WA1871		1	10 units	041
 <p>8WA753</p> <p>Spacer brackets</p> <p>For raised mounting of terminal strips</p>		8WA753		1	50 units	041
 <p>8WA752</p> <p>Spacers</p> <ul style="list-style-type: none"> • With 5.5 mm hole • For raised mounting of terminal strips 		8WA752		1	100 units	041