

# SIRIUS 3SE6 RFID Non-Contact Safety Switches

## Selection

### Selection and ordering data

With M12 connector, 8-pole

Version/coding	Latching / length	DT	Order No.	Price per PU	PU (UNIT, SET, M)	PS*
----------------	-------------------	----	-----------	--------------	-------------------	-----

#### Rectangular safety switches 91 mm x 25 mm



3SE6 315

#### RFID safety switches

- Family coded
  - None
  - With 18 N magnetic catch
- Individually coded, programmable several times
  - None
  - With 18 N magnetic catch
- Individually coded, programmable once
  - None
  - With 18 N magnetic catch

▶	<b>3SE6 315-0BB01</b>	1	1 unit
▶	<b>3SE6 315-1BB01</b>	1	1 unit
▶	<b>3SE6 315-0BB02</b>	1	1 unit
▶	<b>3SE6 315-1BB02</b>	1	1 unit
▶	<b>3SE6 315-0BB03</b>	1	1 unit
▶	<b>3SE6 315-1BB03</b>	1	1 unit




3SE6 310

#### RFID actuators

- Standard
  - None
  - With 18 N magnetic catch

▶	<b>3SE6 310-0BC01</b>	1	1 unit
▶	<b>3SE6 310-1BC01</b>	1	1 unit

#### Optional accessories



3SX5 600-1G

#### Covers and spacers

One pack (1 unit) contains 8 covers and 4 spacers

A	<b>3SX5 600-1G</b>	1	1 unit
---	--------------------	---	--------



3SX5 601-2GA

#### Connecting cables, 8-pole, with 1 straight M12 socket

Rated voltage 30 V  
Rated current 2 A

- Length 3 m
- Length 5 m
- Length 10 m

A	<b>3SX5 601-2GA03</b>	1	1 unit
A	<b>3SX5 601-2GA05</b>	1	1 unit
A	<b>3SX5 601-2GA10</b>	1	1 unit

For monitoring units see Chapter 14, "Industrial Communication"