


Snap-on design holds strap in place!

Pipe Straps — Steel



- Elongated bolt hole makes alignment easy, even when holes in mounting surface are out of alignment
- Available in 1/2" to 2" sizes



Oval Hole for Screw Size (C)




CAT. NO.	HUB SIZE	DIMENSIONS (IN.)		
		A	B	C (BOLT HOLE)
4159	1/2"	1 21/32	3/4	1/4
4160	3/4"	2 1/32	3/4	1/4
4161	1"	2 1/32	3/4	1/4
4162	1 1/4"	2 7/8	3/4	1/4
4163	1 1/2"	3 1/16	1 1/4	1 1/32
4164	2"	4 1/16	1 1/2	1 1/32

Not UL Listed.

CSA File No. 2884 and 4484

Designed to fit each size of conduit snugly!

Pipe Straps — Malleable Iron



- High reinforcing ribs on each side increase strength and reduce weight
- Hot-dipped galvanized finish



Oval Hole for Screw Size (C)



CAT. NO.	HUB SIZE	DIMENSIONS (IN.)		
		A	B	C (BOLT HOLE)
4176	1/2"	2 5/32	2 1/32	1/4
4177	3/4"	2 9/16	1 1/16	1/4
4178	1"	3	3/4	1/4
4179	1 1/4"	3 3/4	1 3/16	5/16
4180	1 1/2"	4 3/16	1 5/16	3/8
4181	2"	5 3/16	1 1/2	7/16
1282	2 1/2"	5 5/16	1 1/2	1/2
1283	3"	6 1/16	1 5/8	1/2
1284	3 1/2"	7 19/32	1 3/4	5/8
1285	4"	8 7/16	1 7/8	5/8

Not UL Listed.

CSA File No. 2884 and 4484

Eliminates the need for costly offset-bending of conduit to prevent corrosive moisture traps when conduit is mounted directly to a surface!


Pipe Spacers



1350



1351



- Used with T&B conduit straps to permit space between conduit and mounting surface
- Pre-mountable and stackable to eliminate offsetting
- Malleable iron construction with hot-dipped galvanized finish

CAT. NO.	HUB SIZE	DIMENSIONS (IN.)	
		A	B
1350	1/2", 3/4", 1"	3"	7/8
1351	1 1/4"-1 1/2"-2"	5"	1 1/16"
1352	2 1/2"-3"	9 9/16"	1 3/4"
1353	3 1/2"-4"	7 7/16"	2"
1354	4 1/2"-5"-6"	10 9/16"	2 5/16"

Conforms to NEC 300-5-C. CSA File No. 2884