

Color-Keyed®

Connectors for Copper Cables — Code and Flex



Two Hole Lugs — Short Barrel for 600V to 35 kV Applications (continued)

Material: High Conductivity Wrought Copper
Finish: Electro Tin Plate

Wire Size ¹		Cat. No.	Bolt Size G	Dimensions (in.)							Die Code	Colour Key
Code	Flex			A	B	C	D	E	F	H		
3/0	2/0 325/24	54266	5/16	2 7/8	1 3/4	15/16	9/64	5/8	11/32	1	50	Orange
		54211	3/8	2 15/16	1 13/16	15/16	9/64	5/8	3/8	1	50	Orange
		54265	1/2	3 15/16	2 13/16	15/16	9/64	5/8	1/2	1 3/4	50	Orange
		256-30695-834	1/2	3 1/4	2 1/16	15/16	9/64	5/8	1/2	1	50	Orange
4/0	3/0 450/24	54212	3/8	3 11/64	1 59/64	1 1/32	9/64	45/64	3/8	1	54	Purple
		54270	1/2	4 1/4	3	1 1/32	9/64	45/64	1/2	1 3/4	54	Purple
		256-30695-1247	1/4	3 1/16	1 7/16	1 1/32	9/64	45/64	3/8	5/8	54	Purple
		256-30695-331	1/4	3 1/16	1 13/16	1 1/32	5/32	45/64	3/8	3/4	54	Purple
		256-30695-1261	5/16	3 1/16	1 13/16	1 1/32	9/64	45/64	5/16	1	54	Purple
4/0	550/24	256-30695-836	5/16	3 1/2	1 61/64	1 15/64	5/32	27/32	1/2	1	62	Yellow
		256-30695-345	3/8	3 3/32	1 11/16	1 1/4	3/16	25/32	3/8	7/8	62	Yellow
		256-30695-399	3/8	4 1/4	2 51/64	1 1/4	5/32	27/32	3/8	1	62	Yellow
		256-30695-452	3/8	3 1/8	1 7/8	1 1/4	5/32	27/32	3/8	7/8	62	Yellow
		58265	1/2	4 3/16	2 13/16	1 3/16	3/16	27/32	1/2	1 3/4	62	Yellow
		256-30695-837	1/2	3 37/64	2 1/16	1 15/64	5/32	27/32	1/2	1	62	Yellow
		256-30695-835	3/8	3 17/32	2 3/64	1 1/4	5/32	27/32	3/8	1	62	Yellow
250 MCM		54213	3/8	3 9/32	1 59/64	1 1/8	9/64	49/64	3/8	1	62	Yellow
		54275	1/2	4 3/16	2 13/16	1 3/32	3/16	49/64	1/2	1 3/4	62	Yellow
300 MCM		256-30695-1262	5/16	3 3/16	1 13/16	1 1/4	5/32	27/32	5/16	1	66	White
		54214	3/8	3 3/8	1 59/64	1 1/4	5/32	27/32	3/8	1	66	White
		54280	1/2	4 29/64	3	1 1/4	5/32	27/32	1/2	1 3/4	66	White
350 MCM	650/24	256-30695-332	1/4	3 1/16	1 13/16	1 5/16	7/32	59/64	3/8	3/4	71	Red
		256-30695-1240	5/16	4 3/16	2 13/16	1 5/16	7/32	15/16	1/2	1 3/4	71	Red
		54215	3/8	3 3/16	1 13/16	1 11/32	13/64	59/64	3/8	1	71	Red
		54282	1/2	4 3/16	2 13/16	1 11/32	13/64	59/64	1/2	1 3/4	71	Red
350/373 925/24		256-30695-439	3/8	4 1/4	2 9/32	1 5/8	1/4	1 3/32	5/8	1	80	N/A
		256-30695-838	1/2	4 1/8	2 5/16	1 5/8	1/4	1 3/32	1/2	1 1/4	80	N/A
		58277	1/2	5	3	1 39/64	11/64	1 7/64	1/2	1 3/4	80	N/A
		256-30695-839	3/8	4 3/32	2 1/16	1 39/64	7/32	1 3/64	1/2	1	80	N/A
400 MCM	313 775/24	256-30695-1263	5/16	3 1/2	1 13/16	1 13/32	11/64	61/64	5/16	1	76	Blue
		256-30695-1375	3/8	3 1/2	1 59/64	1 3/8	11/64	61/64	7/16	1 1/16	76	Blue
		54216	3/8	3 7/8	1 59/64	1 13/32	11/64	61/64	3/8	1	76	Blue
		54283	3/8	3 7/8	1 59/64	1 13/32	11/64	61/64	3/8	1 1/16	76	Blue
500 MCM		256-30695-333	1/4	3 9/16	1 13/16	1 5/8	1/4	1 7/64	3/8	3/4	87	Brown
		54218	3/8	3 59/64	1 59/64	1 39/64	7/32	1 7/64	3/8	1	87	Brown
		54286	1/2	5	3	1 39/64	7/32	1 7/64	1/2	1 3/4	87	Brown
		256-30695-188	1/2	4 1/16	2 5/16	1 5/8	7/32	1 7/64	1/2	1 1/4	87	Brown
600 MCM	444 1100/24	54220	3/8	4 1/16	2	1 3/4	1/4	1 1/4	3/8	1	94	Green
		54289	1/2	5 5/32	3	1 3/4	1/4	1 13/64	1/2	1 3/4	94	Green

Can be used for 600V to 35kV applications provided proper insulation techniques are used.

U.L. and C.S.A. listing of T&B connectors is a continual process; please call your Regional Sales Office for the latest listings.

Many tongue sizes are available undrilled; please call your Regional Sales Office for availability.

¹ Call your Regional Sales Office for sizes not listed.

For tool and die selection see pages 60-61.

