




NON-METALLIC THREADED HARDWARE & SEALANT

NON-METALLIC CABLE TRAY & STRUT SYSTEMS


U-BOLT



Nominal Pipe Size		H Height	Catalogue No.	Design Load A		Design Load B		Max. Torque		Weight / C	
in.	mm	in.		lb.	N	lb.	N	in.-lb.	N-m	lb.	g
1/2	15	2.41	NM-FUB050	300	1334	150	667	30	3.4	3.5	1588
3/4	20	2.60	NM-FUB075	300	1334	150	667	30	3.4	3.9	1769
1	25	2.85	NM-FUB100	300	1334	150	667	30	3.4	4.4	1996
1-1/4	32	3.16	NM-FUB114	300	1334	150	667	30	3.4	4.8	2177
1-1/2	40	3.47	NM-FUB112	300	1334	150	667	30	3.4	5.2	2359
2	50	4.18	NM-FUB200	600	2669	200	890	60	6.8	7.7	3493
2-1/2	65	4.68	NM-FUB212	600	2669	200	890	60	6.8	10.2	4627
3	80	5.31	NM-FUB300	600	2669	200	890	60	6.8	12.6	5715
3-1/2	90	5.81	NM-FUB312	600	2669	200	890	60	6.8	15.1	6849
4	100	6.31	NM-FUB400	600	2669	200	890	60	6.8	17.6	7983

Safety Factor of 3 on Design Load.

CHANNEL NUT



Thread	Cat. No. w/spring	Cat. No. w/o spring	Pull-Out		Slip Resistance		Max. Torque		Weight / C	
			lb.	N	lb.	N	in.-lb.	N-m	lb.	g
3/8 - 16	NM-FCN38	FCN38W0	300	1334	150	667	200	22.6	2.3	1043
1/2 - 13	NM-FCN12	FCN12W0	300	1334	150	667	200	22.6	2.3	1043

Safety Factor of 3 on Design Load.

Note: 1/4" and 5/16" sizes are available.

FLAT WASHER



Hole Size in.	Cat. No.	Weight / C	
		lb.	g
3/8"	NM-F38W	.5	227
1/2"	NM-F12W	.5	227
5/8"	NM-F58W	.5	227
3/4"	NM-F34W	.5	227
1"	NM-F100W	.5	227

SPRAY SEALANT



Spray acrylic to reseal fiberglass after field modifications.

Description	Catalogue No.
12 fl. oz. can	NM-CLEAR-1215

BRUSH-ON RESIN SEAL KIT



To reseal fiberglass after field modifications. Vinyl Ester Resin

Kit Contents

- Resin
- Catalyst
- Stir stick and applicator

Description	Catalogue No.
1/2 pint	NM-RSK-05
1 pint	NM-RSK-10