


## Rigid/Intermediate Grade Conduit Fittings

### Conduit Bushings Die Cast Zinc — Insulated Metallic

- 105°C thermoplastic liners
- Heavy reinforced ribs




CAT. NO.	CONDUIT SIZE (IN.)	DIMENSIONS (IN.)		STD. CTN.
		A	B	
BU-801	½	1.06	0.43	1,000
BU-802	¾	1.31	0.43	1,000
BU-803	1	1.59	0.48	500
BU-804	1¼	1.96	0.56	250
BU-805	1½	2.18	0.60	250

UL File No. E-23018.

CAT. NO.	CONDUIT SIZE (IN.)	DIMENSIONS (IN.)		STD. CTN.
		A	B	
BU-806	2	2.68	0.56	250
BU-807	2½	3.25	0.90	50
BU-808	3	3.87	0.85	25
BU-809	3½	4.37	0.93	25
BU-810	4	5.00	0.93	10

UL File No. E-23018.

### Conduit Bushings Die Cast Zinc — Heavy Reinforced Ribs




CAT. NO.	CONDUIT SIZE (IN.)	DIMENSIONS (IN.)		STD. CTN.
		A (MIN.)	B (MAX.)	
BU201	½	1.05	0.37	1,000
BU-202	¾	1.32	0.37	1,000
BU-203	1	1.58	0.47	500
BU-204	1¼	1.94	0.50	250
BU-205	1½	2.20	0.52	250

UL File No. E-23018.

CAT. NO.	CONDUIT SIZE (IN.)	DIMENSIONS (IN.)		STD. CTN.
		A (MIN.)	B (MAX.)	
BU-206	2	2.69	0.52	250
BU-207	2½	3.23	0.85	50
BU-208	3	3.84	0.85	25
BU-209	3½	4.35	0.85	25
BU-210	4	5.02	0.85	10

UL File No. E-23018.

### Insulated Bushings — Thermoplastic




CAT. NO.	CONDUIT SIZE (IN.)	DIMENSIONS (IN.)		STD. CTN.
		A	B	
BU-501	½	1½/32	1¼/16	400
BU-502	¾	1½/32	1¼/16	400
BU-503	1	¾/16	1¼/16	200
BU-504	1¼	¾/16	1¾/32	100
BU-505	1½	¾/16	2¼/16	100
BU-506	2	¾/16	2¼/16	60

UL File No. E-23018 ½"–4" only.  
Rated 105° C.

CAT. NO.	CONDUIT SIZE (IN.)	DIMENSIONS (IN.)		STD. CTN.
		A	B	
BU-507	2½	2¾/32	3¼/16	20
BU-508	3	¾/16	3¾/32	20
BU-509	3½	¾/16	4¾/64	5
BU-510	4	2¾/32	4¾/32	5
BU-511	5	1	6¼/16	5
BU-512	6	1	7¼/16	5

UL File No. E-23018 ½"–4" only.  
Rated 105° C.

### Bushings — Iron/Zinc Plated



CAT. NO.	CONDUIT SIZE (IN.)	DIMENSIONS (IN.)		STD. CTN.
		A	B	
BU-401	½	1½/32	¾/16	1,000
BU-402	¾	1¼	¾/16	1,000
BU-403	1	1¼/16	¾/16	500
BU-404	1¼	1¼/16	1¾/32	200
BU-405	1½	2¼/64	¾/16	100
BU-406	2	2¼/64	¾/16	50


UL File No. E-23018.

CAT. NO.	CONDUIT SIZE (IN.)	DIMENSIONS (IN.)		STD. CTN.
		A	B	
BU-407	2½	3¼/16	1¼/32	30
BU-408	3	3¾/16	2¾/32	25
BU-409	3½	4¼/16	2¾/32	25
BU-410	4	4¾/32	1¾/16	25
BU-411	5	4¾/32	1¾/16	10

UL File No. E-23018.

### Grounding Bushings Die Cast Zinc — Insulated Metallic With Aluminum Lay-in Type Lug

- 105° C thermoplastic liners
- Heavy reinforced ribs



CAT. NO.	TRADE SIZE (IN.)	GROUNDING LUG WIRE SIZE		STD. CTN.
		MIN.	MAX.	
BG201	½	14	4	500
BG-202	¾	14	4	500
BG-203	1	14	4	250
BG-204A	1¼	14	4	200
BG-204	1¼	8	1/0	200
BG-205A	1½	11	4	100
BG-205	1½	8	1/0	50
BG-206A	1	14	4	100
BG-206	2	8	1/0	50

UL File No. E-3060.

CAT. NO.	TRADE SIZE (IN.)	GROUNDING LUG WIRE SIZE		STD. CTN.
		MIN.	MAX.	
BG-207	2½	8	1/0	50
BG-207A	2½	6	250 kcmil	50
BG-208	3	8	1/0	50
BG-208A	3	6	250 kcmil	50
BG-209	3½	8	1/0	10
BG-209A	3½	6	250 kcmil	10
BG-210	4	8	1/0	10
BG-210A	4	6	250 kcmil	10

UL File No. E-3060.