

Aluminum Mechanical Splice Kits

Range taking — no compression tools and dies required.

Aluminum Flood-Seal® Mechanical Splice Kits

- Prefilled with oxide inhibitor to prevent oxidation and keep out moisture
- Dual-rated and approved for use with aluminum or copper conductors
- EPDM rubber splice covers ensure a fully insulated, watertight repair splice — there's no taping, heat shrink or mastic required
- Sized for most conductors perfect for repairing any 2-, 3- or 4-wire installation
- RUS Accepted



CAT. NO.	CONDUCTOR RANGE	CONNECTOR LENGTH	NUMBER OF SCREWS PER SIDE
Two-Wire Kits			
USK 2/0 (SLOTTED SCREW)	#14-2/0	1½	1
USK 2/0 AH		1½	
USK 4/0	#4-4/0	2	
USK 350*	#6-350	2¼	
USK 350-4		4	
USK 350-12*		12	
USK 350-18*		18	
UH 11		4¼	
UH 11 L†		6½	
USK 350-12 DS	12	2	
USK 350-18 DS†	18		
USK 500	#2-500		4¼
USK 500 L†			7½
USK 500-12†			12
USK 500-16†			16
USK 750	250-750		16¼

* UL Listed.

† Repair kits.

CAT. NO.	CONDUCTOR RANGE	CONNECTOR LENGTH
Compression-Type Repair Kits		
URS 125	#2-350 (standard one-hole lugs)	17½
Three-Wire Kits		
SL 3-2 K	#4-#14 CU / 2-14 AL	3
USK 4/0 SL	Side "A" (#6-350), Side "B" (1/0-4/0 with #6-#14 sol. tap)	Accommodates 3 wires
Four-Wire Kits		
FSS 42-212 AH	#2-#12	4
UH 11 SL	Side "A" (#6-350), Side "B" (1/0-4/0 with #6-#14 sol. tap)	Accommodates 4 wires
MTB 350-1	#6-350	4
MTB 350		