


Tools and Dies

TBM6S Crimp Tool



Creates diamond-style crimp



- Wide ranges of #8 AWG thru 500 kcmil for copper lugs, splices and taps and #10 AWG thru 350 kcmil for aluminum lugs and splices
- Also installs 63105 through 63140 orange, green and blue H-taps
- Shure-Stake® mechanism ensures a properly completed crimp each time
- Comes complete with plastic carrying case and wire brush


Note: The TBM6S tool can also be used to crimp Sta-Kon® terminals. See Sta-Kon® section for dies.

CAT. NO.	COLOR CODE	CAT. NO UPPER DIE	CAT. NO LOWER DIE	PKG. QTY.
TBM6S	RED	13475	13477	1
	BLUE	13475	13477	
	GRAY	13472	13476	
	BROWN	13474	13477	
	GREEN	13474	13477	
	PINK	13475	13477	
	BLACK	13474	13477	
	ORANGE	13474	13477	
	PURPLE	13475	13477	
	YELLOW	13473	13476	
	GOLD	13474	13477	
	TAN	13475	13477	
	OLIVE	13475	13477	
	RUBY	13473	13476	
	WHITE	13473	13476	
	RED	13472	13476	
	BLUE	13472	13476	
BROWN	13478	13478		

Carrying Cases for TBM5S and TBM6S

CAT. NO.	DESCRIPTION	PKG. QTY.
295-31365M	Steel Carrying Case for TBM5S and TBM6S	1
295-31365	Plastic Carrying Case for TBM5S and TBM6S	1

TBM8S Crimp Tool



Creates diamond-style crimp



- Installs code copper lugs and connectors #8 AWG through 500 kcmil
- Installs aluminum lugs and connectors #10 AWG through 350 kcmil
- Shure-Stake® mechanism ensures positive compression
- Included dies are color coded and provide die-code embossing for easy installation and inspection
- Installs all code copper compression joints and small C-taps
- Comes complete with installing dies and wire brush in plastic carrying case

CAT. NO.	COLOR CODE	DIE CAT. NO	PKG. QTY.
TBM8S	RED	13461	1
	BLUE		
	GRAY		
	BROWN	13462	
	GREEN		
	PINK		
	BLACK	13463	
	ORANGE		
	PURPLE		
	YELLOW	13464	
	GOLD		
	TAN		
	OLIVE	13465	
	RUBY		
	WHITE		
	RED	13466	
	BLUE	13467	
BROWN	13468		

Tools and Dies

Dies for Standard Lugs & Splices (TBM45S – TBM12)

CONNECTOR SIZE				TBM8-750M-1 TBM8-750BSCR TBM8-750			TBM-8/8S	TBM-5/5S	TBM6/6S / 25000		13642M / 13400 HYDRAULIC HEAD		TBM12 HYDRAULIC HEAD	
CODE COPPER	FLEX/24	AL/CU	COLOR CODE	TBM45S	TBM4S	TBM8-750	TBM8 DIE CAT. NO.	TBM5 DIE CAT. NO.	CAT. NO. UPPER DIE	CAT. NO. LOWER DIE	DIE CAT. NO.	DIE CODE NO.	DIE CAT. NO.	DIE CODE NO.
#8 AWG	37/24	10 AWG	RED	C-Taps Only	↕	↕	13461	13454	13475	13477	11732	21	TBM12D-1	21
#6 AWG	61/24	#8 AWG	BLUE						13475	13477	11733	24	TBM12D-1	24
#4 AWG	91/24	#6 AWG	GRAY						13472	13476	11734	29	TBM12D-2	29
#2 AWG	125/24		BROWN						13474	13477	11735	33	TBM12D-2	33
#1 AWG	150/24	#4 AWG	GREEN						13474	13477	11736	37	TBM12D-3	37
1/0 AWG	225/24	#2 AWG	PINK						13475	13477	11737	42	TBM12D-3	42
2/0 AWG	275/24		BLACK						13474	13477	11738	45	TBM12D-4	45
3/0 AWG	325/24		ORANGE						13474	13477	11739	50	TBM12D-4	50
4/0 AWG	450/24		PURPLE						13475	13477	11740	54	TBM12D-5	54
250 kcmil	550/24		YELLOW						13473	13476	11771	62	TBM12D-5	62
		#1 AWG	GOLD	13474	13477	11738	45	TBM12D-4	45					
		1/0 AWG	TAN	13474	13477	11739	50	TBM12D-4	50					
		2/0 AWG	OLIVE	13475	13477	11740	54	TBM12D-5	54					
		3/0 AWG	RUBY	13473	13476	11741	60	TBM12D-5	60					
300 kcmil		4/0 AWG	WHITE	13465		11742	66H	TBM12D-5	66H					
350 kcmil	775/24	250 kcmil	RED	13466	13458	13472	13476	11743	71H	TBM12D-4	71H			
400 kcmil	775/24	300 kcmil	BLUE	13467	4/0 only	13472	13476	11744	76H	TBM12D-4	76H			
	925/24*		N/A			13479	13476	11745	80H					
			N/A											
500 kcmil		350 kcmil	BROWN	13468		13478	13478	11746-TB	87H	TBM12D-3	87H			
600 kcmil	1100/24	400 kcmil	GREEN					11747	94H	TBM12D-3	94H			
			GREEN								94H			
	1325/24**		PINK											
700 kcmil		500 kcmil	PINK					11748	99H	TBM12D-2	99H			
750 kcmil		650 kcmil	BLACK					11749	106H	TBM12D-2	106H			
800 kcmil			ORANGE					11750	107H					
		700 kcmil	PURPLE					11751	112H	TBM12D-1	112H			
900 kcmil	1925/25	750 kcmil	YELLOW					11753	115H	TBM12D-1	115H			
1000 kcmil		800 kcmil												
		1000 kcmil												

* Standard barrel only. Long barrel requires Brown 87H.

** Standard barrel only. Long barrel requires Brown 106H.

Dies for Standard Lugs & Splices (OD58)

CONNECTOR SIZE				OD58	
CODE COPPER	FLEX/24	AL/CU	COLOR CODE	DIE CAT NO.	DIE CODE NO.
#8 AWG	37/24	#10 AWG	RED	BY15C	21
#6 AWG	61/24	#8 AWG	BLUE	BY17C	24
#4 AWG	91/24	#6 AWG	GRAY	BY19C	29
#2 AWG	125/24		BROWN	BY21C	33
#1 AWG	150/24	#4 AWG	GREEN	BY53C	37
1/0	225/24	#2 AWG	PINK	BY23C	42
2/0	275/24		BLACK	BY28C	45
3/0	325/24		ORANGE	BY25C	50
4/0	450/24		PURPLE	BY27C	54
250 kcmil	550/24		YELLOW	BY31C	62
		#1 AWG	GOLD	BY24C	45
		1/0	TAN	BY25C	50
		2/0	OLIVE	BY31C	54
		3/0	RUBY	BY32C	60

Tools and Dies

Connectors & Grounding — Blackburn® Compression Connectors Featuring the Color-Keyed® System

Dies for Standard Lugs & Splices (BPLT6BSCR – 21940)

CONNECTOR SIZE			COLOR CODE	BPLT6BSCR/TBM6H				BPLT6BSCR/ BPLT62BSCR			
CODE COPPER	FLEX/24	AL/CU		DIE CAT. NO.	DIE CODE NO.	HEX-FLEX® DIE CAT. NO.	HEX-FLEX® DIE CODE NO.	DIE CAT. NO.	DIE CODE NO.	HEX-FLEX® DIE CAT. NO.†	HEX-FLEX® DIE CODE NO.
8 AWG	37/24	10 AWG	RED	6TON21	21	6TON21X	21X	TBM6221	21	TBM6221X	21X
6 AWG	61/24	8 AWG	BLUE	6TON24	24	6TON24X	24X	TBM6224	24	TBM6224X	24X
4 AWG	91/24	6 AWG	GRAY	6TON29	29	6TON29X	29X	TBM6229	29	TBM6229X	29X
2 AWG	125/24		BROWN	6TON33	33	6TON33X	33X	TBM6233	33	TBM6233X	33X
1 AWG	140/24	4 AWG	GREEN	6TON37	37	6TON37X	37X	TBM6237	37	TBM6237X	37X
1/0	225/24	2 AWG	PINK	6TON42	42	6TON42X	42X	TBM6242	42	TBM6242X	42X
2/0	275/24		BLACK	6TON45	45	6TON45X	45X	TBM6245	45	TBM6245X	45X
3/0	325/24		ORANGE	6TON50	50	6TON50X	50X	TBM6250	50	TBM6250X	50X
4/0	450/24		PURPLE	6TON54	54	6TON54X	54X	TBM6254	54	TBM6254X	54X
250 kcmil	550/24		YELLOW	6TON62	62	6TON62X	62X	TBM6262	62	TBM6262X	62X
		1 AWG	GOLD	6TON45	45	6TON66X	66X	TBM6245	45		
		1/0	TAN	6TON50	50			TBM6250	50		
		2/0	OLIVE	6TON54	54			TBM6254	54		
		3/0	RUBY	6TON60	60			TBM6260	60		
300 kcmil		4/0	WHITE	6TON66	66H			TBM6266	66	TBM6266X	66X
350 kcmil	775/24 (short)	250 kcmil	RED	6TON71	71H			TBM6271	71		
400 kcmil	775/24 (long)	300 kcmil	BLUE	6TON76	76H			TBM6276	76		
	925/24*			6TON80	80H			TBM6280	80		
500 kcmil		350 kcmil	BROWN	6TON87	87H			TBM6287	87		
600 kcmil	1100/24	400 kcmil	GREEN	6TON94	94H						
			GREEN								
700 kcmil	1325/24**	500 kcmil	PINK		99H						
750 kcmil		650 kcmil	BLACK		106H						
800 kcmil			ORANGE		107H						
		700 kcmil	PURPLE		112H						
900 kcmil	1925/24	750 kcmil	YELLOW		115H						
1000 kcmil		800 kcmil	N/A								
		1000 kcmil	N/A								

*Standard barrel only. Long barrel requires Brown 87H.

**Standard barrel only. Long barrel requires Black 106H.

***15500 Series dies require 15500-TB adapter. 15500F for full-size die to fit TBM15I without adapter.

† HEX-FLEX® Dies are sold separately in halves. The catalog numbers shown in the chart above are for the upper half of the die.

For the bottom half (the indenter), order one Cat. No. 6TONX for all 6TONX Series, one Cat. No. TBM62X for all TBM62X Series Die Codes 21X–66X, one Cat. No. 15500X for 15500X Series Die Codes 21X–94X and one Cat. No. 15600X for all 15600X Series Die Codes 62X–115X.

Dies for Standard C-Taps

CONNECTOR	COLOR CODE	TBM25S DIE NO.	TBM5/5S DIE NO.	TBM6/6S DIE NO.	TBM8/8S DIE NO.	BPLT6BSCR BPLT62BSCR DIE NO.	TBM6H/BPLT6BSCR DIE NO.
54705	RED	Red Nest	13454	13475/13477	13461	TBM6221	6TON21
54710	BLUE	Blue Nest	13454	13475/13477	13461	TBM6224	6TON24
54715	GRAY	Grey Nest	13454	13472/13476	13461	TBM6229	6TON29
54720	BROWN	Brown Nest	13454	13474/13477	13461	TBM6233	6TON33
54725	GREEN	Green Nest	13455	13474/13477	13462	TBM6237	6TON37
54730	PINK	—	13455	13475/13477	13462	TBM6242	6TON42
54735	BLACK	—	13455	13474/13477	13462	TBM6245	6TON45
54740	ORANGE	—	13455	13474/13477	13462	TBM6250	6TON50
54745	PURPLE	—	13456	13475/13477	13463	TBM6254	6TON54
54750	YELLOW	—	13456	13473/13478	13463	TBM6262	6TON62