

## Device Boxes

### Armoured and Nonmetallic Sheathed Cable Clamps



**BC2104-LLE**

Holding prongs and prepositioned depth tabs.



**BC2304-LHTQ**

One screw mounting. Provision for external nailing. Positioning tabs for 1/2 in. and 3/4 in. drywall.



**BC2104-LX**

Self-locking spring clamps. Holding prongs and prepositioned depth tabs. Raised ground screws. **Approved for nonmetallic sheathed cable only.**



**BC2104-LN**

Staked nails. Holding prongs and prepositioned depth tabs.



**BC2104-LRB**

Flat sides for rework applications. 1 gang.




**BC2104-LLE-2**

2 gang. Holding prongs and prepositioned depth tabs.




**BC2104-LRB-2**

Flat sides for rework applications. 2 gang.



**BC2104-LLE-3**

3 gang. Holding prongs and prepositioned depth tabs.




**BC2104-LLE-4**

4 gang. Holding prongs and prepositioned depth tabs.



**BC2304-LHTQ-2**

2 gang. Holding prongs and prepositioned depth tabs.



**BC2304-LHTQ-3**

3 gang. Holding prongs and prepositioned depth tabs.



**BC2304-LHTQ-4**

4 gang. Holding prongs and prepositioned depth tabs.



Cat. No.	Width (in.)	Volume (Cu. in.)	Features		Pryouts ends
			Ears	Bracket	
<b>2-1/2 in. Deep — Non-Gangable — 3 in. High</b>					
<b>BC2104-LLE</b>	2	12.5	-	P. Tabs	4
<b>BC2104-LLE-2</b>	3-3/4	25.0	-	P. Tabs	8
<b>BC2104-LLE-3</b>	5-1/2	37.5	-	P. Tabs	12
<b>BC2104-LLE-4</b>	7-3/8	50.0	-	P. Tabs	16
<b>BC2104-LN</b>	2	12.5	-	P. Tabs/Nails	4
<b>BC2104-LX</b>	2	12.5	-	P. Tabs	4
<b>BC2304-LHTQ</b>	2	14.5	-	P. Tabs	4
<b>BC2304-LHTQ-2</b>	3-3/4	27.0	-	P. Tabs	8
<b>BC2304-LHTQ-3</b>	5-1/2	39.5	-	P. Tabs	12
<b>BC2304-LHTQ-4</b>	7-3/8	52.0	-	P. Tabs	16
<b>BC2104-LRB</b>	2	12.5	-	-	4
<b>BC2104-LRB-2</b>	3-3/4	25.0	-	-	8