

ACS® Aluminum Wiring (Brown)


The Marrette® ACS® Aluminum Wiring wire connector is a fixed spring, twist-on connector made of special spring wire materials and coatings, to meet the rigorous standards for aluminum wire connections.

External Cap

- Made of sturdy, thermoplastic valox resin 150°C rated.
- Large, finely ribbed, “barrel-shaped” cap - makes it easier to grip even when hands are greasy or damp.
- Deep, wide throat ensures full insulation coverage.
- Threaded entry helps guide large wire bundles right into the spring.

Inner Spring

- Made of a special bronze alloy and then plated with a thick coating of tin to satisfy the rigorous standards established for aluminum wire connections.
- Round spring design ensures that aluminum conductors and highly stranded copper wires are not scored or severed when joined.
- Approved for circuits up to 600 V, and lighting fixtures and signs up to 1000 V.
- Approved for aluminum-to-aluminum, copper-to-copper, aluminum-to-copper (or highly stranded copper) connections.
- Convenient packaging - sized right and job-site ready!
- Not UL listed.



ACS® Aluminum Wiring (Brown)

Ordering Information

Model	Colour	AWG Wire Range							
		22	20	18	16	14	12	10	8
63	brown			Min.: 1 #18 + 1 #14	Max.: 1 #18 + 4 #14				
65	brown			Min.: 2 #14	Max.: 3 #16 + 3 #12				

Note: Refer to pages A26 to A28 for related Wire Combination Reference Guides

Packaging Options



	Cat. No.	Packaging Format	Quantity per Package	Std. Pkg. (Min./Mult.)
63	63C	Card (Retail market only*)	6/Card	20 Cards
	63B	Window Box (Retail market only*)	25/Box	10 Boxes
	63P	Propak	100	1,000 Units
	63D	Flip-Pak	500	500 Units
65	65C-CDN	Card (Retail market only*)	6/Card	20 Cards
	65P	Propak	100	1,000 Units
	65D	Flip-Pak	500	500 Units

* Retail: Order 1 each for one (1) Card/Box/Flip-Pak