

Device Boxes – Available Models

Technical Specifications

		Gangable														Non-Gangable						
Depth		1 1/2	2	2	2	2 1/4	2 1/2	2 1/2	2 1/2	2 1/2	2 1/2	2 1/2	3	3	3	2 1/4	2 1/2	2 1/2	2 1/2	2 3/4	2 1/2	
Cu. in.		8.0	10.0	10.0	12.0	10.0	12.5	12.5	14.5	12.5	12.5	16.0	18.0	15.0	18.0	18.0	11.0	12.5	14.5	15.0	18.5	25.0
Series # BC/CI		1100	1102	425	3102	775	525	1104	1304	4104	4304	3104	1804	1004	1018	3004	777	2104	2304	1504	2004	4204
Conduit Knockouts	Basic Model		✓	✓				✓						✓								
	B							✓														
	K							✓														
	KSSX											✓										✓
	KSS1X-1											✓										
	LE							✓														
	SB		✓					✓														
	SSX				✓								✓									
Nonmetallic Sheathed Cable Clamps (Loomex, NMD90)	L	✓	✓	✓		✓	✓	✓		✓				✓								
	LB							✓						✓								
	LD					✓																
	LH	✓										✓	✓	✓		✓					✓	
	LHT							✓														
	LHTQ								✓				✓			✓			✓			
	LLE	✓																✓		✓		
	LHTQ-2/LLE-2																	✓		✓		
	LHTQ-3/LLE-3																	✓		✓		
	LHTQ-4/LLE-4																	✓		✓		
	LMS								✓										✓			
	LN																	✓		✓		
	LRB																✓					
	LRE	✓																				
	LRW								✓													
	LSSX											✓	✓				✓		✓			✓
	LSS2X																	✓		✓		
LSS3X																	✓		✓			
LSSX-1																✓						
LSS1X-1																	✓		✓			
LSS2X-1																	✓		✓			
Armoured Cable Clamps (BX, AC90)	LX																✓				✓	
	LA							✓		✓												
	LBA							✓														
	LHA							✓				✓	✓	✓							✓	
	LLEA																	✓				
	LLEA-2																	✓				
	LMSA							✓														
	LSBA							✓														
	LSSAX				✓							✓	✓					✓		✓		✓
	LSSA-2X																	✓				
	LSSA-3X																	✓				
	LSSAX-1																✓					✓
	LSSA1X-1											✓										

Device Boxes

Armoured and Nonmetallic Sheathed Cable Clamps

			
CI775-L	BC775-LD	BC777-LRB	CI525-L
Flush ears.	"Swing-arm" rework brackets. Max. wall thickness: 3/4 in.	Pivoting ends for rework installation. Max. wall thickness: 1-1/8 in. * Non-Gangable	"Screwlok" brackets for rework installation. Max. wall thickness: 5/8 in.
			
BC1104-LB	BC1104-LHT	CI1104-LMS	BC1104-L
	Positioning tabs. Provision for external nailing. Two embossed mounting slots for internal screw installation.	Mounting strap with prongs. Recessed 1/2 in.	Flush ears.
			
BC1104-LRB	BC1104-LRW	BC1104-LSSX	BC1304-LHTQ
Flat sides for rework applications.	Rework bracket for closed wall applications. Max. wall thickness: 1 in.		One screw mounting. Provision for external nailing. Positioning tabs for 1/2 in. and 3/4 in. drywall.



Cat. No.	Volume (Cu. in.)	Features		Pryouts ends	Knockouts 1/2 in. bottom
		Ears	Bracket		
2-1/4 in. Deep — Gangable — 3 in. x 2 in. - For use with nonmetallic sheathed cable only					
CI775-L	10.0	flush	-	4	1
BC775-LD	10.0	flush	rework	4	1
BC777-LRB*	11.0	-	rework	4	1
2-1/2 in. Deep — Gangable — 3 in. x 2 in.					
CI525-L	12.5	flush	rework	4	-
BC1104-L	12.5	flush	-	4	-
BC1104-LB	12.5	-	"B"	4	-
BC1104-LHT	12.5	-	P. Tabs	4	-
CI1104-LMS	12.5	-	"MS"	4	-
BC1104-LRB	12.5	flush	-	4	-
BC1104-LRW	12.5	flush	rework	4	-
BC1104-LSSX	12.5	-	"SSX"	4	-
BC1304-LHTQ	14.5	-	P. Tabs	4	-