



Fittings and Brackets

90° Fittings


AB201
 AB201HDGC
 AB201EG
 AB201
 AB201SS6C
 Wt./C 35 lb.




AB202
 AB202HDGC
 AB202EG
 AB202
 AB202SS6C
 Wt./C 35 lb.




AB203
 AB203HDGC
 AB203EG
 AB203
 AB203SS6C
 Wt./C 58 lb.




AB204
 AB204HDGC
 AB204EG
 AB204
 AB204SS6C
 Wt./C 58 lb.




AB205
 AB205HDGC
 AB205EG
 AB205
 AB205SS6C
 Wt./C 78 lb.




AB213
 AB213HDGC
 AB213EG
 AB213
 Wt./C 125 lb.



AB214
 AB214HDGC
 AB214EG
 AB214
 AB214SS6C
 Wt./C 125 lb.




AB216
 AB216HDGC
 AB216EG
 AB216SS6C
 Wt./C 135 lb.




AB252

Cat. No.	A (in.)	Wt./C lb.
AB252-1*	3-7/8	61
AB252-2*	5-7/8	84
AB252-3*	7-7/8	107
AB252-4*	9-7/8	130


*Finishes
 • HDGC • EG • GoldGalv®




AB254R
 AB254RHDGC
 AB254REG
 AB254R
 Wt./C 105 lb.




AB254L
 AB254LHDGC
 AB254LEG
 AB254L
 Wt./C 105 lb.




AB260R
 AB260RHDGC
 AB260REG
 AB260R
 Wt./C 58 lb.




AB260L
 AB260LHDGC
 AB260LEG
 AB260L
 Wt./C 58 lb.



AB274
 AB274HDG
 AB274EG
 AB274
 Wt./C 70 lb.



AB275
 AB275HDGC
 AB275EG
 AB275SS6C
 Wt./C 77 lb.



Standard Dimensions	Value
Hole Spacing	→ 13/16 in. From End
Hole Spacing	→ 1-7/8 in. Centers
Hole Size	→ 9/16 in. Diam.
Material	→ 1-5/8 in. Width
Material	→ 1/4 in. Thick

Materials	Value
HDG(C)	→ Hot-Dipped Galvanized
EG(C)	→ ElectroGalvanized
(No suffix)	→ GoldGalv®
SS6(C)	→ Stainless Steel 316