

## Manual and Power-Assisted Compression Tools

### TBM8-750M-1 12-Ton Dieless Manual Hydraulic Smart™ Tool

**Specifications**

- Installing Range:  
Up to 900 kcmil copper lugs & splices  
Up to 750 kcmil aluminum lugs & splices
- Output Force: 12-Ton
- Dimensions (L x W): 21-1/2 in. x 4-7/32 in.



Creates  
Indent-style  
crimp

Cat. No.	Description	Pkg. Qty.
<b>TBM8-750M-1</b>	12-Ton Dieless Manual Hydraulic Compression Tool	1

### Battpac™ LT TBM8-750BSCR 12-Ton Dieless Battery-Powered Smart™ Tool

**Specifications**

- Installing Range:  
Up to 900 kcmil copper lugs & splices  
Up to 750 kcmil aluminum lugs & splices
- Min. of 40 crimps (4/0 AWG per battery charge)
- Output Force: 12-Ton
- Dimensions (L x W x H): 19-1/2 in. x 3-7/8 in. x 8-1/2 in.
- Battery: Ni-MH 14.4 V 3.0 Ah
- Weight with Battery: 9 lb.



Creates  
Indent-style  
crimp

Cat. No.	Description	Pkg. Qty.
<b>TBM8-750BSCR</b>	12-Ton Dieless Battery-Powered Compression Tool. Includes carrying case, charger, two batteries and carry strap.	1

### TBM8-750 12-Ton Dieless Smart™ Hydraulic Head

**Specifications**

- Installing Range:  
Up to 900 kcmil copper lugs & splices  
Up to 750 kcmil aluminum lugs & splices
- Output Force: 12-Ton
- Operating Pressure: 10,000 psi nominal
- Dimensions (L x W x H): 14-1/2 in. x 4-7/32 in. x 2-9/16 in.
- Weight: 9 lb.



Creates  
Indent-style  
crimp

Cat. No.	Description	Pkg. Qty.
<b>TBM8-750</b>	12-Ton Dieless Hydraulic Compression Head	1

## Options

Cat. No.	Description
<b>TBM8-750G</b>	Field compression gauging kit for above tools
<b>TBM8-750C20</b>	Die set installs Cat. No. 54720 copper "C" taps
<b>TBM8-750C2530</b>	Die set installs Cat. Nos. 54735, 54730 copper "C" taps
<b>TBM8-750C3540</b>	Die set installs Cat. Nos. 54735, 54740 copper "C" taps

Cat. No.	Description
<b>TBM8-750C4550</b>	Die set installs Cat. Nos. 54735, 54750 copper "C" taps
<b>TBM8-750CL</b>	Die set installs Cat. No. 54755 through 54775 copper "C" taps
<b>TBM8-750HG</b>	Die set installs Cat. No. 63110 through 63118 and 63125 copper "H" taps
<b>TBM8-750HB</b>	Die set installs Cat. No. 63140 through 63148 copper "H" taps