

Nonmetallic Sheathed Cable

Accessories



Cat. No.	Dimensions (in.)		Hole Size (in.)	Suggested Application NMD90 (Iomex)
	H	W		
Cable Straps (Aluminum)				
CI0	0.44	0.63	3/16	14/3-12/3
CI1	0.50	0.56	3/16	10/3
CI1-C	0.50	0.50	3/16	14/2-12/2; 14/3-12/3
CI2	0.50	0.63	3/16	14/3-10/3
CI3	0.57	0.68	3/16	14/3-10/3
CI4	0.81	1.06	3/16	4/3
CI5	1.06	1.25	7/32	3/3-2/3
CI10	0.19	0.44	3/16	14/2
CI11	0.31	0.56	3/16	12/2-10/2
Nailing Straps (Zinc Plated Steel)				
CI1544	0.25	0.51	-	14/2-12/2
Nailing Straps (Polyethylene)				
CI1544-P**	0.25	0.49	-	14/2-12/2
CI1546-P**	0.25	0.75	-	14/2-8/2
Cable Staples (Galvanized Steel)				
CIS-1	0.25	0.48	-	14/2-12/2
CIS-2	0.44	0.54	-	2 cables 14/2; 2 cables 12/2; 14/2-14/3-12/2-12/3-10/2-10/3
CIS-3*	0.49	0.70	-	10/2-8/2; 14/3-10/3
CIS-4*	0.76	0.86	-	14/2 - 8/2, 14/3 - 8/3, 14/4 - 10/4
Double Cable Staples (Galvanized Steel)				
CIS-1X2	0.25	0.48 x 2	-	14/2-12/2
CIS-1X2-FP3				
CIS-1X2-FP5				

*Also suitable for application AC90(BX). See page D8.
 Also suitable for NMWU90 of equivalent diameters.
 ** cULus Listed



Cat. No.	Suggested Application
Protector Plates (Galvanized Steel)	
CI66	For wood stud
CI66-FPP	For forenze
CI66-PPH	For exterior wall, in front of wood stud
CI66-SS	For metal stud
CI66-T	For wood stud
CI66-XL	
CI66-XL-2	

As required by CEC rules 12-516 and 12-616