

## Nonmetallic Sheathed Cable

### Accessories



Cat. No.	Dimensions (in.)		Hole Size (in.)	Suggested Application NMD90 (Iomex)
	H	W		
<b>Cable Straps (Aluminum)</b>				
CI0	0.44	0.63	3/16	14/3-12/3
CI1	0.50	0.56	3/16	10/3
CI1-C	0.50	0.50	3/16	14/2-12/2; 14/3-12/3
CI2	0.50	0.63	3/16	14/3-10/3
CI3	0.57	0.68	3/16	14/3-10/3
CI4	0.81	1.06	3/16	4/3
CI5	1.06	1.25	7/32	3/3-2/3
CI10	0.19	0.44	3/16	14/2
CI11	0.31	0.56	3/16	12/2-10/2
<b>Nailing Straps (Zinc Plated Steel)</b>				
CI1544	0.25	0.51	-	14/2-12/2
<b>Nailing Straps (Polyethylene)</b>				
CI1544-P**	0.25	0.49	-	14/2-12/2
CI1546-P**	0.25	0.75	-	14/2-8/2
<b>Cable Staples (Galvanized Steel)</b>				
CIS-1	0.25	0.48	-	14/2-12/2
CIS-2	0.44	0.54	-	2 cables 14/2; 2 cables 12/2; 14/2-14/3-12/2-12/3-10/2-10/3
CIS-3*	0.49	0.70	-	10/2-8/2; 14/3-10/3
CIS-4*	0.76	0.86	-	14/2 - 8/2, 14/3 - 8/3, 14/4 - 10/4
<b>Double Cable Staples (Galvanized Steel)</b>				
CIS-1X2	0.25	0.48 x 2	-	14/2-12/2
CIS-1X2-FP3				
CIS-1X2-FP5				

\*Also suitable for application AC90(BX). See page D8.  
 Also suitable for NMWU90 of equivalent diameters.  
 \*\* cULus Listed



Cat. No.	Suggested Application
<b>Protector Plates (Galvanized Steel)</b>	
CI66	For wood stud
CI66-FPP	For forenze
CI66-PPH	For exterior wall, in front of wood stud
CI66-SS	For metal stud
CI66-T	For wood stud
CI66-XL	
CI66-XL-2	

As required by CEC rules 12-516 and 12-616

## Armoured Cable / Flexible Conduit

### Accessories



Cat. No.	Trade Size (in.)		Clamping Range (in.)	
	EMT	Flex.	Min.	Max.
<b>E.M.T / Flex. Couplings (Zinc Alloy)</b>				
CI5153	1/2	3/8	0.17	0.63
CI5154		1/2	0.75	0.95
TX-212	3/4	3/4	0.78	1.20



Cat. No.	Dimensions (in.)		Hole Size (in.)	Suggested Application AC90 (BX)	Flex. Conduit (in.)
	H	W			
<b>Cable Straps (Aluminum)</b>					
CI0	0.44	0.63	3/16	14/2	—
CI1	0.50	0.56	3/16	12/2-10/2; 14/3-12/3; 14/4	5/16
CI2	0.50	0.63	3/16	10/3; 12/4	3/8
CI3	0.57	0.68	3/16	10/2; 10/3; 12/4	—
CI4	0.81	1.06	3/16	6/2; 6/3; 8/4	1/2
CI5	1.06	1.25	7/32	4/2-2/2; 4/3-2/3; 6/4-4/4	3/4
<b>Cable Staples (Galvanized Steel)</b>					
CIS-3	0.49	0.70	—	14/2-12/2; 14/3-12/3	5/16
CIS-4	0.76	0.86		14/2-8/2; 14/3-8/3; 14/4-10/4	3/8, 7/16

CIS-3 / CIS-4



CI38



Cat. No.	Trade Size (in.)	Max. Flex. Conduit Dia. (in.)	Hole Size (in.)
<b>Flexible Conduit Strap (Galvanized Steel)</b>			
CI38	3/8	0.61	3/16

CI7538



Cat. No.	Max. Flex. Conduit Dia. (in.)	Hole Size (in.)
<b>One Hole Double Sided Strap (Galvanized Steel)</b>		
CI7538*	1.05	3/16

\* Any combination of 3/8 in., 1/2 in. and 3/4 in. EMT, rigid conduit, flexible conduit or teck cables