

Device Boxes

Armoured and Nonmetallic Sheathed Cable Clamps












			
CI775-L	BC775-LD	BC777-LRB	CI525-L
Flush ears.	"Swing-arm" rework brackets. Max. wall thickness: 3/4 in.	Pivoting ends for rework installation. Max. wall thickness: 1-1/8 in. * Non-Gangable	"Screwlok" brackets for rework installation. Max. wall thickness: 5/8 in.
			
BC1104-LB	BC1104-LHT	CI1104-LMS	BC1104-L
	Positioning tabs. Provision for external nailing. Two embossed mounting slots for internal screw installation.	Mounting strap with prongs. Recessed 1/2 in.	Flush ears.
			
BC1104-LRB	BC1104-LRW	BC1104-LSSX	BC1304-LHTQ
Flat sides for rework applications.	Rework bracket for closed wall applications. Max. wall thickness: 1 in.		One screw mounting. Provision for external nailing. Positioning tabs for 1/2 in. and 3/4 in. drywall.



Cat. No.	Volume (Cu. in.)	Features		Pryouts ends	Knockouts 1/2 in. bottom
		Ears	Bracket		
2-1/4 in. Deep — Gangable — 3 in. x 2 in. - For use with nonmetallic sheathed cable only					
CI775-L	10.0	flush	-	4	1
BC775-LD	10.0	flush	rework	4	1
BC777-LRB*	11.0	-	rework	4	1
2-1/2 in. Deep — Gangable — 3 in. x 2 in.					
CI525-L	12.5	flush	rework	4	-
BC1104-L	12.5	flush	-	4	-
BC1104-LB	12.5	-	"B"	4	-
BC1104-LHT	12.5	-	P. Tabs	4	-
CI1104-LMS	12.5	-	"MS"	4	-
BC1104-LRB	12.5	flush	-	4	-
BC1104-LRW	12.5	flush	rework	4	-
BC1104-LSSX	12.5	-	"SSX"	4	-
BC1304-LHTQ	14.5	-	P. Tabs	4	-

* Non-Gangable

Rework Boxes

					
CI425	CI425-L	CI525-L	BC775-LD	BC777-LRB	
"Screwlok" brackets for rework installation. Max. wall thickness: 5/8 in.	"Screwlok" brackets for rework installation. Max. wall thickness: 5/8 in.	"Screwlok" brackets for rework installation. Max. wall thickness: 5/8 in.	"Swing-Arm" rework brackets. Max. wall thickness: 3/4 in.	Pivoting ends for rework installation. Non-gangable. Max. wall thickness: 1-1/8 in.	
					
BC1004-LRB	BC1104-LRB	BC1104-LRW	BC2104-LRB	BC2104-LRB-2	BC54151-LD
Flat sides for rework applications.	Flat sides for rework applications.	Rework bracket for closed wall applications. Max. wall thickness: 1 in.	Flat sides for rework applications. 1 gang.	Flat sides for rework applications. 2 gang.	"Swing-Arm" rework brackets. Max. wall thickness: 3/4 in. Maximum load capacity: 12 lb. (5.5 kg)



Cat. No.	Volume (Cu. in.)	Dimensions H x W x D (in.)	Features Clamps	Knockouts		Pryouts		
				ends	bottom	ends	sides	bottom
Device Boxes								
CI425	10.0	3 x 2 x 2	-	2	1	-	-	-
CI425-L	10.0	3 x 2 x 2	Loomex/BX	-	-	4	-	-
CI525-L	12.5	3 x 2 x 2-1/2	Loomex/BX	-	-	4	-	-
BC775-LD	10.0	3 x 2 x 2-1/4	Loomex	-	1	4	-	-
BC777-LRB*	11.0	3 x 2 x 2-1/4	Loomex	-	1	4	-	-
BC1004-LRB	15.0	3 x 2 x 3	Loomex/BX	-	1	4	-	-
BC1102-LRB	10.0	3 x 2 x 2	Loomex/BX	-	-	4	-	-
BC1104-LRB	12.5	3 x 2 x 2-1/2	Loomex/BX	-	-	4	-	-
BC1104-LRW	12.5	3 x 2 x 2-1/2	Loomex/BX	-	-	4	-	-
BC2104-LRB*	12.5	3 x 2 x 2-1/2	Loomex/BX	-	-	4	-	-
BC2104-LRB-2*	25.0	3 x 4 x 2-1/2	Loomex/BX	-	-	8	-	-
Octagonal Boxes								
BC54151-LD	15.0	4 x 4 x 1-1/2	Loomex/BX	-	1	-	4	4

* Non-Gangable