










Device Boxes

Armoured and Nonmetallic Sheathed Cable Clamps

				
BC3104-LH	BC3104-LHTQ	BC3104-LSSX	CI3104-LSS1X-1	
Positioning tabs. Provision for external nailing.	One screw mounting. Provision for external nailing. Positioning tabs for 1/2 in. and 3/4 in. drywall.	"Wraparound" bracket for 2-1/2 in. and 3-5/8 in. steel studs. With integral support bracket.	"Wraparound" bracket for 2-1/2 in. and 3-5/8 in. steel studs. With integral support bracket. Brackets positioned for 2 layers of 1/2 in. drywall.	
				
BC1304-LHT	CI1804-LH	BC2004-LH	BC2004-LHTQ	CI2016-LX
Provision for external nailing.	Positioning tabs. External nailing. Mounting slots for internal screw installation. X-Cube adds 5.5 cu. in.	Provision for external nailing. Holding prongs and prepositioned depth tabs on one side.	Internally embossed slots for screw mounting. Fixed positioning tabs for single 1/2 in. drywall along with retractable positioning tabs for double 1/2 in. drywall applications. Fixed positioning tabs for outside wall applications. Holding prongs. One screw mounting.	Self-locking spring clamps. Holding prongs and prepositioned depth tabs on one side. Approved for nonmetallic sheathed cable only.



Cat. No.	Volume (Cu. in.)	Features		Pryouts ends
		Ears	Bracket	
2-1/2 in. Deep — Gangable — 3 in. x 2 in.				
BC3104-LH	16.0	-	P. Tabs	4
BC1304-LHT	14.5	-	P. Tabs	4
BC3104-LHTQ	16.0	-	P. Tabs	4
BC3104-LSSX	16.0	-	"SSX"	4
CI3104-LSS1X-1	16.0	-	"SSX"	4
CI1804-LH	18.0	-	P. Tabs	4
2-3/4 in. Deep — Non-Gangable — 3-3/4 in. x 2-3/16 in.				
BC2004-LH	18.5	-	P. Tabs	4
BC2004-LHTQ	20.5	-	P. Tabs	4
2-1/2 in. Deep — Non-Gangable — 3-3/4 in. x 2 in.				
CI2016-LX	18.5	-	P. Tabs	4

