









## Device Boxes

### Armoured and Nonmetallic Sheathed Cable Clamps

			
<b>CI1504-LSSAX</b>	<b>CI3104-LHA</b>	<b>BC3104-LSSAX</b>	<b>BC3104-LSSAX-5/8</b>
"Wraparound" bracket for 2-1/2 in. and 3-5/8 in. steel studs. With integral support bracket.	Positioning tabs. Provision for external nailing.	"Wraparound" bracket for 2-1/2 in. and 3-5/8 in. steel studs. With integral support bracket.	Brackets for use with 5/8 in. drywall.
			
<b>CI3104-LSSA1X-1</b>	<b>BC3104-LSSX</b>	<b>CI2004-LHA</b>	<b>CI1004-LHA</b>
1 in. recessed brackets for 2-1/2 in. and 3-5/8 in. steel studs. Brackets positioned for 2 layers of 1/2 in. drywall.	"Wraparound" bracket for 2-1/2 in. and 3-5/8 in. steel studs. With integral support bracket.	Provision for external nailing. Holding prongs and prepositioned depth tabs.	Positioning tabs. Provision for external nailing. Two embossed mounting slots for internal screw installation.



Cat. No.	Volume (Cu. in.)	Features		Pryouts ends
		Ears	Bracket	
<b>2-1/2 in. Deep — Non-Gangable — 3 in. x 2-1/4 in.</b>				
<b>CI1504-LSSAX</b>	15.0	-	"SSX"	4
<b>2-1/2 in. Deep — Gangable — 3 in. x 2 in.</b>				
<b>CI3104-LHA</b>	16.0	-	P. Tabs	4
<b>BC3104-LSSAX</b>	16.0	-	"SSX"	4
<b>BC3104-LSSAX-5/8</b>	16.0	-	"SSX"	4
<b>CI3104-LSSA1X-1</b>	16.0	-	"SSX"	4
<b>BC3104-LSSX</b>	16.0	-	P. Tabs	4
<b>2-3/4 in. Deep — Non-Gangable — 3-3/4 in. x 2-3/16 in.</b>				
<b>CI2004-LHA</b>	18.5	-	P. Tabs	4
<b>3 in. Deep — Gangable — 3 in. x 2 in.</b>				
<b>CI1004-LHA</b>	15.0	-	P. Tabs	4