

RACK MOUNTED POWER SOLUTIONS



Rack Mounted Power Solutions are designed to fit a standard 19" rack. The compact 1U design takes up a minimum amount of rack space

CODE REFERENCE

cULus Listed: File E66421
Guide XBYS2, XUHT2, VZCA2

NOTE: We are continually upgrading circuitry and features to provide the best possible power distribution solutions; therefore, the products in this section of the catalog may change without notice. Contact the factory for additional information.

Sentrex® High Performance Surge Specifications

| | |
|----------------------------|---|
| Surge Protection Circuitry | 3 Element, 3-Stage Hybrid Circuit |
| Maximum Surge Current | 56,000 Amps (32,000 Amps L-N, 12,000 Amps L-G, 12,000 Amps N-G) |
| Noise Reduction | +50dB |
| Response Time | Less than 1 nanosecond |

Perma-Power® Computer Grade Surge Specifications

| | |
|----------------------------|---|
| Surge Protection Circuitry | Single Stage |
| Maximum Surge Current | 36,000 Amps (12,000 Amps L-N, 12,000 Amps L-G, 12,000 Amps N-G) |
| Noise Reduction | +35dB |
| Response Time | Less than 1 nanosecond |

NOTE: See the Joule explanation on page 626.

Mounting Information


MOUNTING TYPES

Each Rack Mounted Power Solution can be mounted to standard 19" [482mm] racks via the closed slots. Power Commander High Amperage Unit can also be mounted in a 0U position as shown below. Complete mounting hardware and installation instructions are included with every unit.

Rack Mounting

Fits standard 19" [482mm] rack.

Hardware not included.




Designed in accordance with E.I.A. standards.

RACK MOUNTED POWER SOLUTIONS

Surge Protected and Power Only Products


Surge Protected Products Ordering Information

R5S, R5S-15 Plug-In Outlet Center Unit




Six rear outlets, lighted switch, 15A. 6' [1.8m] (R5S) or 15' [4.6m] (R5S-15) cord. Sentrex® high performance surge protection.

R8BZ, R8BZ-15 Plug-In Outlet Center Unit




Eight rear outlets, lighted switch, 15A. Receptacles rotated 90° and 4 outlets spaced to accommodate transformers. 6' [1.8m] (R8BZ) or 15' [4.6m] (R8BZ-15) cord. Perma Power® computer grade surge protection.

R5BZ, R5BZ-15 Plug-In Outlet Center Unit




Six rear outlets, lighted switch, 15A. 6' [1.8m] (R5BZ) or 15' [4.6m] (R5BZ-15) cord. Perma Power® computer grade, surge protection.

R5BZX, R5BZX-15 Plug-In Outlet Center Unit




Six rear outlets, 15A. 6' [1.8m] (R5BZ) or 15' [4.6m] (R5BZ-15) cord. Perma Power® computer grade, surge protection.

R5BZ20, R5BZ20-15 Plug-In Outlet Center Unit



Six 20A rear outlets, on/off switch. 6' [1.8m] (R5BZ20) or 15' [4.6m] (R5BZ20-15) cord. Perma Power® computer grade surge protection.


R5BZ20X, R5BZ20X-15 Plug-In Outlet Center Unit



Six 20A rear outlets. 6' [1.8m] (R5BZ20X) or 15' [4.6m] (R5BZ20X-15) cord. Perma Power® computer grade surge protection.


Power Only Products Ordering Information

J08B0B, J08B2B Plug-In Outlet Center Unit




Eight rear outlets, lighted switch, 15A, receptacles rotated 90° and 4 outlets spaced to accommodate transformers. 6' (J08B0B) or 15' (J08B2B) [1.8m or 4.6m] cord. Receptacle center-to-center 1 1/2" [38mm] and 2" [51mm].

J06B0B, J06B2B Plug-In Outlet Center Unit




Six rear outlets, lighted switch, 15A, 6' (J06B0B) or 15' (J06B2B) [1.8m or 4.6m] cord. Receptacle center-to-center 1 1/2" [38mm].

J60B0B, J60B2B Plug-In Outlet Center Unit




Six front outlets, lighted switch, 15A, 6' (J60B0B) or 15' (J60B2B) [1.8m or 4.6m] cord. Receptacle center-to-center 1 1/2" [38mm].

J24B0B, J24B2B Plug-In Outlet Center Unit



Two front, four rear outlets, lighted switch, 15A, 6' (J24B0B) or 15' (J24B2B) [1.8m or 4.6m] cord. Receptacle center-to-center 1 1/2" [38mm].

J06B0BX, J06B2BX Plug-In Outlet Center Unit



Six rear outlets, 15A, 6' (J06B0BX) or 15' (J06B2BX) [1.8m or 4.6m] cord. Receptacle center-to-center 1 1/2" [38mm].